

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7108)

Set a Yew post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., marked 1/4 S on N. face, from which
A Fir 30" dia., bears S.63°E., 32 lks. dist. mkd. 1/4 S BT
A Fir 36" dia., bears North, 34 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Sept. 3, 1959 - C.S. File 42/356-13

Determined by O.B.Ts:
40" Fir bears North 22.4 ft.
30" Fir bears S.63°E., 21.1 ft., found scribe.
At corner point, Set 3/4" x 30" Iron pipe, from which
3" Alder bears S.71°E., 31.0 ft. mkd. 1/4 S35 BT.
50" Fir bears S.50°E., 25.0 ft., bark scribed 1/4 S35 BT.
Shively Creek bears West 250.0 ft. dist.

Kristian DeGroot - Richard Bennett - 11/2006 - M146-49

Set - 1 1/4"x30" iron post, 22" in the ground, with a 2 1/2" brass cap stamped:

T30S R4W
1/4 S 26
S 35

2006
PLS 1941

From which the original BTs by Bushey in 1893:

A 36" fir stump with healed blaze bears N.5°30'E., 22.4 ft to a cotton gin spike set in the center of the stump. (Record North)

A 20" fir stump with opened blaze bears S.67°45'E., 21.1 ft to a cotton gin spike set in the center of the stump. (Record S.63°E.)

And a bearing tree by Markham in 1959:

A 50" fir stump with bark blaze visible bears S.55°E., 23.3 ft. (Record S.50°E., 25.0 ft)

New - A 10" D.Fir bears N.46°15'W., 15.3 ft scribed "1/4 S26 BT".

A 11" D.Fir bears S.25°45'W., 13.3 ft scribed "1/4 S35 BT".

A 5/8"x30" iron rod with plastic cap mkd "BTS ENG-SURV" bears S.67°36'00"E., 19.08 ft.

A 5/8"x30" iron rod with plastic cap mkd "BTS ENG-SURV" bears S.49°12'08"E., 15.27 ft.

Fd BC, 5 BTs, 2 I.R.s, & steel post by R. Rice 8/3/2012 - C.S. file 65/77-20