TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6994)

Set ¼ sec. post at average distance, from which
A B.Oak 20" dia., bears N.27°W., 163 lks. dist.
A W.Oak 10" dia., bears S.38°E., 182 lks. dist.

((*NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7043* - "I was unable to discover any sign of blaze along the whole line. The topography given in field notes of original surveys mentions a bottom 25.00 chs. long, while I found the whole line to run on top of a high, rough, timbered mountain - - - - -"

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Pages 7042-43)

Set a Maple post 3 ft. long, 3" sq., 24" in the ground, for the ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 6" dia., bears S.56½°W., 34 lks. dist. mkd. ¼ S BT
A Fir 10" dia., bears N.6¾°W., 38 lks. mkd. ¼ S BT.

BLM resurvey by James E. Jelley, Cadastral Surveyor - under Group #1070, surveyed June 1981/May 1982 - (DCSO records Vol. 43 Page(s) 16809-10)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 30 S R 4 W

1/4 $\frac{S\ 23}{S\ 26}$

1981

from which
A Fir 8" dia., bears N.51¼°E., 11 lks. dist. mkd. ¼ S23 BT
A Fir 10" dia., bears S.8°E., 20 lks. dist. mkd. ¼ S26 BT.

Mark Smalley - 5/2000 - C.S. File 65/33-17

Found - 1981 IPBC
14" Fir N.51¼°E. 7.3'. Good condition, healed blaze.
14" Fir S.8°E., 13.2'. Good condition, healed blaze.
New BTs- 20" Fir, S.85°W., 22.0 scribed "¼ S BT"
16" Fir, S.36°E., 35.0 scribed "¼ S BT"

FD. Ok by K. DeGroot, 11/2006 - M146-49
Fd. Ok by R. Rice 11/2010 - M161-47