

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6996)

Set $\frac{1}{4}$ sec. post at average distance, from which
A Laurel 4" dia., bears S.75°W., 75 lks. dist.
A Laurel 4" dia., bears N.5°W., 60 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7049-50)

Set a Fir post 3 ft. long, 3" sq., 24" in the ground, marked $\frac{1}{4}$ S on N. face, from which
A Laurel 8" dia., bears S.34 $\frac{1}{2}$ °W., 10 lks. dist. mkd. $\frac{1}{4}$ S BT.
A Laurel 7" dia., bears N.6 $\frac{1}{4}$ °W., 36 lks. dist. mkd. $\frac{1}{4}$ S BT.

Note, the old post and bearing trees could not be found, as this locality has been burnt over, destroying all small trees.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - June 1963 - C.S. File 53/26-58

Found both original BTs, each shows good scribing.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 4 W
 $\frac{1}{4}$ S 11
S 14
1963

New BTs -12" R.Fir bears N.74°W., 23.0 ft. scribed $\frac{1}{4}$ S11 CS BT.

16" R.Fir bears S.8°E., 23.0 ft. scribed $\frac{1}{4}$ S14 CS BT.

Corner is on spur, course N.45°W.

Fd. BC & Accessories per renewal notes, 3/2013 - R. Quimby, M157-70