TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6990)

Set ¼ sec. post, from which
A W.Oak 7" dia., bears S.60°W., 29 lks. dist.
A B.Oak 15" dia., bears N.50°E., 13 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7036)

1/4 sec. cor. post is gone, but both bearing trees, mkd. ¼ S BT are standing. I restore this cor. by setting a W.Oak post, 4 ft. long, 4" sq., 24" in the ground, mkd. ¼ S on W. face, from which
A W.Oak 9" dia., bears S.60°W., 29 lks. dist. mkd. ¼ S BT
A B.Oak 18" dia., bears N.50°E., 13 lks. dist. mkd. ¼ S BT
These are the old bearing trees, which I re-mark as the old marks are dim.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18651)

Point for the ¼ sec. cor. of secs. 13 and 14, determined by the method of irregular boundaries: there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd. T 30 S R 4 W

¼
S 14 S 13
1988

from which
A Fir 10" dia., bears S.47°E., 57 lks. dist. mkd. ¼ S13 BT
A Fir 9" dia., bears N.11°W., 63 lks. dist. mkd. ¼ S14 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.