

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6990)

-----  
Set post cor. of secs. 11, 12, 13 and 14, from which  
A Red Fir 15" dia., bears S.5°W., 55 lks. dist.  
A Red Fir 5" dia., bears S.85°E., 37 lks. dist.  
A Red Fir 6" dia., bears N.30°W., 35 lks. dist.  
A Red Fir 18" dia., bears N.3°E., 97 lks. dist.  
A white rock on head of South Myrtle Creek, course N.23°E.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7034-35)

-----  
The post set for this cor. is gone but all bearing trees are standing, to-wit

- A Fir 18" dia. mkd. S 14 BT.
- A Fir 7" dia. mkd. S 13 BT.
- A Fir 8" dia. mkd. S 11 BT.
- A Fir 20" dia. mkd. S 12 BT.

I restore this cor. by setting a basalt rock, 24x11x6, 18" in the ground, marked with 1 notch on E. and 4 notches on S. edges, from which

- A Fir 20" dia., bears N.5°E., 97 lks. dist. mkd. T30S R4W S12 BT.
- A Fir 7" dia., bears S.85°E., 37 lks. dist. mkd. T30S R4W S13 BT.
- A Fir 18" dia., bears S.5°W., 55 lks. dist. mkd. T30S R4W S14 BT.
- A Fir 8" dia., bears N.53°W., 35 lks. dist. mkd. T30S R4W S11 BT.

These are the old bearing trees, the marks of which being dim, I re-marked.

Fd. and tied in GLO resurvey by Wm. F. briggs, U.S. Deputy Surveyor, under special instructions dated Aug. 7, 1891 (DCSO records, Vol. 17 Pages 7102-03)

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18651-52)

-----  
The sec. cor., monumented with the basalt stone, 24 x 11 x 6 ins., loosely set by Thiel, projecting 16" above ground, with 3 notches on S. edge and 1 notch on E. edge, with top corner chipped off, from which the remains of an original bearing tree:

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears N.53°W., 35 lks. dist. with decayed fir alongside, size indeterminate, with scribe marks OS visible on decayed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 30 S R 4 W  
S 11 \* S 12  
S 14 \* S 13  
1988

from which new bearing trees:

A Fir 14" dia., bears N.25¼°E., 26 lks. dist. mkd. T30S R4W S12 BT.

A Fir 8" dia., bears S.31¼°E., 15 lks. dist. mkd. T30S R4W S13 BT.

A Fir 15" dia., bears S.53 3/4°W., 44 lks. dist. mkd. T30S R4W S14 BT.

A Fir 15" dia., bears N.81¼°W., 58 lks. dist. mkd. T30S R4W S11 BT.

Deposit white "DEEP-1" magnetic marker at base and the marked stone alongside the stainless steel post.

Fd. BC & Accessories per renewal notes, 3/2013 - R. Quimby, M157-70