

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6991)

Set post cor. of secs. 1, 2, 11 and 12, from which
A Red Fir 7" dia., bears S.43°W., 9 lks. dist.
A Red Fir 8" dia., bears N.85°W., 20 lks. dist.
A Red Fir 4" dia., bears N.15°E., 21 lks. dist.
A Maple 4" dia., bears S.45°E., 20 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7037-38)

The post set for this cor. is gone. The only bearing tree standing is the Fir in Sec. 2, mkd. S2 BT; Fir stumps in Secs. 1, 11, and 12, corresponding in size and direction with the trees in those secs. described in the furnished field notes, give additional evidence. I restore this cor. by setting a Fir post, 4 ft. long, 4" sq., 24" in the ground, mkd. T30S S1 on NE.; R4W S12 on SE.; S11 on SW.; S2 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which

A W.Fir 8" dia., bears N.67°E., 20 lks. dist. mkd. T30S R4W S1 BT.
A Red Fir 36" dia., bears S.6°E., 51 lks. dist. mkd. T30S R4W S12 BT.
A Red Fir 24" dia., bears S.82°W., 52 lks. dist. mkd. T30S R4W S11 BT.
A Red Fir 14" dia., bears N.85°W., 20 lks. dist. mkd. T30S R4W S2 BT. This is the old bearing tree, whose marks being dim, I re-mark.

Cor. used and tied by Wm. F. Briggs, U.S. Deputy Surveyor, under special instructions, dated Aug. 7, 1891 - (DCSO records, Vol. 17 Page 7104)

F.C. Frear, Deputy Co. Surveyor - Wit: A. Wallenburg, R. Morrison - Oct/Nov. 1918 - Vol. 3 Pg. 29; C.S. File 7/18; M 1-3

Renew from old BTs.
Set in 6" x 6" x 18" conglomerate SandStone and remark all old gov. bearing trees.

Ben B. Irving, Douglas Co. Surveyors Office - Wit: Earnest Brown; Joe Snyder - Nov. 19, 1934 - C.S. File 37/19

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found conglomerate rock 6" x 6" x 18".
Marked - A 6" W.Fir, N.45°E., 7 ft.
An 8" W.Fir, S.62°W., 23 ft.
A 24" Fir N.89°W., 13 ft. (Orig. BT)
A 6" W.Fir S.42°E., 2.5 ft.

Ben B. Irving, Douglas Co. Surveyors Office - Wit: J. Byron;
Ray Irving - Nov. 16, 1953 - C.S. File 45/219

Identified corner from:
24" Fir N.85°W., 20 lks., chopped out old scribe visible.
36" Fir S.82°W., 52 lks., stump checks for bearing and
distance.
36" Fir S.6°E., 51 lks., stump checks for bearing and
distance.
Also found lower part of orig. stake when we excavated for
monument.
Set 1" Iron pipe with brass cap mkd. County Surv. Off. 1, 2,
11, 12 T30S R4W 1953.
Blazed and scribed 4 new bearing trees;
8" R.Fir N.15°E., 91.2 ft. mkd. T30S R4W S1 CS BT.
16" W.Fir N.58°W., 41.6 ft. mkd. T30S R4W S2 CS BT, brass
plate.
18" R.Fir S.25°W., 116.5 ft. mkd. T30S R4W S11 CS BT.
12" R.Fir S.65°E., 25.3 ft. mkd. T30S R4W S12 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike
Darby; Wm. S. Stoffel crew - June 1963 - C.S. File 53/26-110

Found Brass cap at corner and all bearing trees. SW. BT, now
stump.
New BT - 12" Maple S.72°W., 57.0 ft., scribed S11 CS BT.

Douglas Co. Surveyors Office - A. Victor Cangie; Jim H. Cook,
crew - march 11, 1976 - C.S. File 59/8-9

Found - 8" R.Fir now 16", bears N.15°E., 91.2 ft. Good scar
and alive and well.
16" W.Fir stump bears N.58°W., 41.6 ft. No scribing
visible but fit well for bearing and distance.
12" R.Fir now 19", bears S.65°E., 25.3 ft. Shows
good scar and alive and well.
36" R.Fir stump bears S.6°E., 36.7 ft. No scribing
visible but fit for bearing and distance. Stump
is decayed and rotten
No trace of any other monument.
At corner point, SET 1" x 30" I.P. with brass cap stamped:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Douglas County Surveyor
 T 30 S R 4 W

S 2	S 1
S 11	S 12

 1976

New BTs -7" W.Fir bears S.45°W., 41.1 ft. mkd. "T30S R4W S11 CS BT" in a double blaze.
 16" W.Fir bears N.2½°W., 59.6 ft. mkd. "T30S R4W S1 CS BT" in a double blaze.
 Corner is 100 ft. off Days Creek Road under a N-S fence bordering E.R. Hall's pasture. Fence borders E. side of pasture.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Nov. 15, 1984 - C.S. File 62/21-43

Found - 1976 DCSO brass cap on 1¼" I.P. firmly set, protruding 5" from ground. Cap properly mkd. Earlier monuments probed for, no evidence found. All original, 1854, BTs searched for, no evidence found.

1889, 1891 BT, 36" R.Fir, now a decayed 38" DBH, 4 ft. tall stump bearing S.06°E., 35.2 ft. - 33.7 ft. slope dist. to face (Rec. S.6°E., 33.7 ft.) Tree has possible evidence of a healed blaze. This is opened to reveal decayed interior of stump, no evidence of face or scribing found.

8" R.Fir now 20" DBH Grand Fir, bears N.15°E., 91.2 ft. Tree has well healed double blaze.

16" W.Fir now 19" dia., 1 ft. tall decayed Fir stump, bears N.58°W., 41.6 ft. Tree has remains of lower blaze with scribing "BT" visible. (Brass plate found healed in lower blaze; now in DCSO artifact display)

12" R.Fir now 24" DBH D.Fir bears S.67½°E., 25.3 ft. (Rec. S.65°E. 25.3 ft.) Tree has well healed double blaze with no scribing visible.

7" W.Fir now a 9" dia. 12" tall W.Fir stump, bears S.45°W., 39.7 ft. (39.7 ft. reduced from 40.6 ft. slope dist., tag on cut portion of tree with same date as 1976 Co. visit, has distance mkd. as 40.6 ft.) Open portion of upper blaze has scribing "30 S 4" visible; there is also a lower healed blaze.

16" W.Fir now a 17" DBH Grand Fir bears N.2½°W., 59.6 ft. Tree has marking "30SR4WS2 CS" visible in a partially healed double blaze.

No evidence found from 1934 renewal or New BT from 1963. (Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BT - 8" DBH D.Fir scribed "T30S R4W S12 CS BT" on a double blaze, bears S.12°E., 17.0 ft.
Monument lies approx. 100 ft. South of Days Creek Rd. #34.
Monument lies 3 ft. East of a N-S fence line.

Fd. BC & Accessories per renewal notes, 3/2013 - R. Quimby, M157-70