

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6992)

Set ¼ sec. post at proper distance and made a trench and drove a charged stake in the center as per instructions. Wilson's house, S.44°W.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7040)

Set a sand rock 15x8x6 ins., 10" in the ground, marked ¼ S on W. face; dug pits 18x18x12 ins. N. and S. of stone, 5½ ft. dist., and raised a mound of earth, 1½ ft. high, 3½ ft. base along side.

F.C. Frear - Deputy Co. Surveyor - For: H. & A. Wollenberg Ranch - Nov. 1918 - M 1-3; Vol. 3 Pg. 29; C.S. File 7/18

4" x 40" Cedar stake.

(On old visual map is the symbol for "looked for, not found". Could not find DCSO record source for this symbol. Probably a County search)

Corner searched for, not found.