

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION C C for Secs. 1 and 2 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7041)

I set a Cedar post 4½ ft. long, 4" sq., 24" in the ground, for closing cor. to secs. 1 and 2, T30S R4W, marked C C T30S S1 on SE.; R4W S2 on SW. faces, and 6 notches on S. and 1 on E. edges, from which

A B.Oak 30" dia., bears S.75°E., 43 lks. dist. mkd. T30S R4W S1 BT.

A W.Oak 8" dia., bears S.40 ¾°W., 87 lks. dist. mkd. T30S R4W S2 BT.

F.C. Frear, Deputy Co. Surveyor - Wit: A. Wallenburg; R. Morrison - Oct/Nov. 1918 - Field book 14=45; C.S. File 7/18; Vol. 3 Pg. 29-30; M 1-3

Renew this corner from old BTs. Set in 1¼" x 36" Iron pipe, from which

A 40" W.Oak bears N.46°W., 56½ lks.

A 10" W.Oak stump bears S.75°E., 43 lks.

And the ¼ corner on the So. side of Sec. 36 bears East 30 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-134

Found - 1" I.Pipe at corner and BTs as recorded by Frear, 1918.

New BTs -9" Laurel bears S.3°W., 14.7 ft. scribed S2 T30S R4W CS BT.

11" W.Oak bears S.76°W., 33.5 ft. scribed S2 CS BT.

Ron Rice, Ward NW Inc. - For: Seneca Jones Timber Co. - June 2003 - M142-46

Found - 1¼" Iron pipe, bent.

Set - "T" post adjacent to both pipe.