

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6876)

-----  
Set a post, cor. of secs. 1, 6, 31 and 36, from which  
A Laurel 6" dia., bears S.75°E., 26 lks. dist.  
A Laurel 9" dia., bears N.60°E., 34 lks. dist.  
A Laurel 8" dia., bears N.15°W., 50 lks. dist.  
A Laurel 8" dia., bears S.30°W., 40 lks. dist.

-----  
GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 16 Page(s) 6892) and "tied" in Vol. 17 Pgs. 7016-17 and Pg. 7029)

-----  
At the cor. to Tps. 30 and 31 S., Rs. 3 and 4 W. the post of which is gone, but the following bearing trees are standing:  
A Laurel 10" dia. mkd. T30S R3W S31 BT.  
A Laurel 9" dia., mkd. T30S R4W S36 BT.  
A Laurel 9" dia., mkd. T30S R4W S1 BT.  
A Laurel stump in sec. 6 corresponding in size and direction with description of field notes. I restore this cor. by setting a Laurel post, 4½ ft. long, 4" sq., 24" in the ground mkd. T30S S31 on NE.; R3W S6 on SE.; T31S S1 on SW.; R4W S36 on NW. faces, with 6 notches on each edge, from which  
A Laurel 10" dia., bears N.60°E., 34 lks. dist. mkd. T30S R3W S31 BT.  
A Laurel 9" dia., bears S.31°W., 40 lks. dist. mkd. T31S R4W S1 BT.  
A Fir 12" dia., bears S.51°E., 45 lks. dist. mkd. T31S R3W S6 BT.  
A Laurel 9" dia., bears N.16°W., 50 lks. dist. mkd. T30S R4W S36 BT.  
The Laurels are the original bearing trees, which I remember.

-----  
GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7798)

-----  
As the old cor. established for the cor. to tps. 30 and 31 S., Rs. 3 and 4 W., is not the cor. to tp. 31 S., Rs. 3 and 4 W.; I destroy the marks on the SE. and SW. faces of the post cor. and also the marks on the Fir and Laurel witness trees S. of the cor. in T31S R4W.

(Cor. also tied by Wm. Bushey, on Pg. 7812) and Pg. 6904)

-----  
John H. Markham, Jr. - For: Stomar Lbr. Co. - Wit: R.G. Boyd - April 29, 1959 - C.S. File 42/356-11

-----  
Cor. determined by O.B.T.s. (Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE tsp cor)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

13" Laurel bears S.31°W., 26.4 ft., found scribe.  
13" Laurel bears N.16°W., 33.0 ft., found scribe, remarked "S36 T30S BT".  
24" Fir bears S.51°E., 29.7 ft. - I bark scribed "S31 T31S BT"  
At corner point, SET 1" x 30" Iron rod, from which  
7" Chinquapin bears N.43°W., 47.0 ft. mkd. S36 R4W BT.  
30" Fir bears N.40°E., 17.0 ft. mkd. S31 T30S BT.  
9" Laurel bears N.80°E., 45.0 ft. mkd. S31 T30S R3W BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - March 1963 - C.S. File 52/138-49

-----  
Found - 1" I.Bar at corner and BTs as recorded by Markham. Orig. 13" (now), Laurel N.16°W., 33.0 ft. bark scribed. We rescribe wood, "T30S R4W S36 CS BT". Chinquapin to NW. now dead.

BLM resurvey by Wayne L. Rogers; Rick A. McMullen; Lance J. Bishop, Cadastral Surveyors under Group #1217, surveyed Sept. 1984/ April 1986 - (DCSO records Vol. 47 Page(s) 18129)

-----  
The cor. of Tps. 30 S., Rs. 3 and 4., perpetuated and recorded by Markham in 1959, monumented with an iron rod, 1" dia., firmly set, projecting 15" above ground, from which the remains of the original bearing trees:

A decayed Madrone stump, size indeterminate, bears S.30°W., 39 lks. dist. with fragmentary scribe marks visible on decayed blaze. (Rec. S.31°W., 40 lks.)

A Madrone 18" dia., bears N.16°W., 48½ lks. dist., remarked by Markham, with scribe marks T31S S1 visible on bark blaze. (Rec. 50 lks.)

and a bearing tree mkd. by Thiel

A Fir 40" dia., bears S.51°E., 45 lks. dist., with scribe marks T31S S1 visible on bark blaze.

and bearing trees mkd. by Markham

A Fir 47" dia., bears N.41°E., 25½ lks. dist., with scribe marks T30S R 31 BT visible on bark blaze.

A Madrone 12" dia., bears N.80°E., 67½ lks. dist. with healed blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, directly over iron rod, with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>T 30 S R 4 W   R 3 W <u>S 36</u>   <u>S 31</u> S 1 T 31 S   R 4 W 1985</p>
<p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p>
<p>David Edwards - For: Rome Creek Timber LLC - Sept. 2011 - M162-72</p> <p style="text-align: center;">-----</p> <p>Found - 50" Fir stump N.41°E., 16.8' 42" Fir S.51°E., 29.7' bark blazed. 22" Madrone w/tag N.16°W., 32.0'</p> <p>Set - 6' steel post 2' north on line</p>