

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700134

PRIMARY CORNER DESCRIPTION CC Tsp cor S 31, T30-4; S 6, T31-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Wm. Thiel, under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Pages 7023-24)

-----  
Intersect offset of the Meridian line 495 lks. South of the 1/4 sec. cor. bet. 36 and 31, T30S, Rgs. 4 & 5.  
Set A Fir post, 4½ ft. long 4" sq., 24" in the ground, for closing cor. of Tps. 30 & 31, R.4W., marked T30S S31 on N., R4W on E., T31S S6 on S. faces, with 6 notches on N., E. and S. faces, from which  
    A Laurel 8" dia., bears N.52°E., 31 lks. dist., mkd. T30S R4W S31 BT.  
    A Fir 20" dia., bears S.53½°E., 72 lks. dist., mkd. T31S R4W S6 BT.  
(Standing in a grove of tall Laurels from 6 to 8 ins. in dia.)

GL0 resurvey by Wm. M. Bushey under Contract #620 dated June 17, 1893 (DCSO records, Vol. 17 Pages 7126-27)

-----  
CC which is a post, 4" sq., firmly set. The marks are destroyed by a recent fire. I find one witness tree. I remove this post Cor. and set a Fir post, 4" sq., 4 ft. long, 24" in the ground for closing corner to Tps. 30 and 31 S., R 4 W. marked C C R4W on E., T30S S31 on N. and T31S S6 on S. faces with 6 notches on N., S., and E. faces; from which  
    A Laurel 8" dia., bears N.52°E., 31 lks. dist. mkd. T30S R4W S31 BT. This tree is dead.  
The other bearing trees are burnt down. I mark 3 new witness trees:  
    Fir 12" dia. bears N.55°E., 74 lks. dist., mkd. T30S R4W S31 BT.  
    Fir 14" dia., bears S.83 3/4°E., 71½ lks. dist., mkd. T31S R4W S6 BT.  
    Pine 18" dia., bears S.23½°W., 38 lks. dist., mkd. T30 and 31 C C R4W BT.

Doug. County Surveyors Office - April 11, 1957 - C.S. File 47/175-2

-----  
Found - Trees to NE and SE alive and in good condition, showing good scars.  
    The Pine to the SW has been cut but stump still in place. Chopped out pine stump and found old face with traces of scribe marks. Face is charred and has evidently been burned, destroying most of the scribe marks.  
At intersection of distances from BTs and stump, found bearings to agree with Gov't field notes. (Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700134

PRIMARY CORNER DESCRIPTION CC Tsp. Cor., S 31 T30-4; S 6 T31-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set a 1" Iron pipe with brass cap mkd:	County Surveyor's CC T30S   T30S R5W   S 31 R4W S36   S 6 T31S Office 1957
Mark one new BT: 10" madrone N.50°W., 21.2 ft. scribed T30S R5W S36 CSBT	
Fd. brass cap & 4 BTs, April 1996 by Ken Hoffine - M 123-69	
DCS0-GIS Corner visitation - 6/21/2005 - Typed: 2/8/2011 - C.S. File 67/33-1	
Monument - 1¼"	Comment - needs rehab
Ken Hoffine - For: Lone Rock Timber Co. - Nov. 2013 - M 166-6 & C.S. File 65/81-1	
From the Narrative: "Based on computations from our previous survey M123-69 we established the true corner location of the SW corner of sec. 31, 6.46 ft westerly on line between the fd SW closing corner of sec. 31 and the angle point shown."	
Found - 1957 county cap with a record of N.89°35'17"E., 6.46 ft of true position Rotten remains bears S.23°W., 25.1 ft (record S.23½°W., 25.4 ft) visible scribing 22" D.Fir bears N.54½°E., 49.1 ft (record N.54½°E., 49.2 ft) healed face and tag 18" Madrone stump 3.5 ft tall bears N.52¼°W., 20.9 ft as per record. 24" D.Fir stump bears S.83¾°E., 47.2 ft as per record chopped out face and tag corner lies approx. 150 feet South of 31-5-12.1 road, in small stand of older BLM timber.	
BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCS0 records Vol. 59 Page 23831-2)	
The amended closing cor of T30 & 31S R4W bears S.89°25'21"W., 6.48 ft. perpetuated by Byron, in 1957; monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with a brass cap (properly) marked. (Continued next page)	

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 700134

PRIMARY CORNER DESCRIPTION CC Tsp cor S 31, T30-4; S 6, T31-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which the remains of the BTs mkd. by Bushey in 1893  
A fir, 22" dia., bears N.55°E., 48.8 ft., with a healed blaze.

A decayed fir stump, 23" dia., bears S.83¾°E., 47.2 ft., with scribe marks R4W S6 visible on open blaze.

A decayed pine stump, size indeterminate, bears S.23½°W., 25.1 ft., with illegible scribe marks visible on open blaze.

and the remains of a BT mkd. by Byron

A madrone stump with strong regrowth, 20" dia., bears N.51°W., 21.1 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., flush with the surface of the ground, with brass cap mkd.

AM  
T 30 S  
R5W | R4W  
C S 31  
S 36 | C S 6  
T31 S  
2019

Buried the iron post, 36" long, alongside the stainless steel post.