

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T30-3

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6874)

Set a post, cor. of secs. 19, 24, 25 and 30, from which
A Laurel 18" dia., bears S.45°E., 40 lks. dist.
A Laurel 10" dia., bears N.40°E., 33 lks. dist.
A Laurel 9" dia., bears N.50°W., 19 lks. dist.
A Laurel 10" dia., bears S.47°W 36 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 16 Page(s) 6895) and (Vol. 17 Pgs. 7030-31)

The post, set for this cor. is lying down, decayed, but all four bearing trees are still standing and easily identified. I restore this cor. by setting a W.Oak post 4½ ft. long, 4" sq., 24" in the ground mkd. T30S S19 on NE.; R3W S30 on SE.; R4W S25 on SW.; S25 on NW. faces, with 4 notches on N. and 2 notches on S. edges, from which
A Laurel 14" dia., bears N.40°E., 33 lks. dist. mkd. T30S R3W S19 BT.
A Laurel 24" dia., bears S.45°E., 40 lks. dist. mkd. T30S R3W S30 BT.
A Laurel 10" dia., bears N.50°W., 19 lks. dist. mkd. T30S R4W S24 BT.
A Laurel 14" dia., bears S.47°W., 36 lks. dist. mkd. T30S R4W S25 BT.
All of which I remark, the old marks being overgrown and dim.

GLO survey by William F. Briggs, U.S. Deputy Surveyor, under special instructions dated Aug. 7, 1891 - (DCSO records Vol. 17 Page(s) 7101)

Cor. to secs. 19 and 30, T30S R3W bears N.2°00'E., 27.96 chs. (from sec. cor. 24 & 25 only T30-4) as established by W. Thiel. Post and BT standing.

Ben B. Irving, County Surveyor - Arthur Evans, Milo Godfrey, Frnaklin Smith, crew - Nov./Dec. 1948 - C.S. File 43/6 and M 15-60

Location determined from orig. BTs.
Set 1½" x 30" Iron pipe for corner, from which
20" Laurel N.40°E., 33 lks., alive. (Orig.)
30" Laurel S.45°E., 40 lks., alive. (Orig.)
18" Laurel N.50°W., 19 lks., alive. (Orig.)
14" Laurel S.47°W., 36 lks., dead. (Orig.)
(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 700328

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs, blazed and scribed
10" Chinquapin N.31½°W., 16.7 ft.
12" Fir S.72½°W., 50.2 ft.
No suitable trees in Secs. 19 & 30.

BLM survey by Wayne L. Rogers; Lance J. Bishop; James L. White, Cadastral Surveyors, under Group #1133, surveyed June 1983/Dec. 1984 - (DCSO records Vol. 47 Page(s) 17849)

The cor. of secs. 19 and 30 only, perpetuated and recorded by Irving in 1948, monumented with an iron pipe 1¼" dia., firmly set, projecting 2" above ground, from which the remaining original bearing trees

A Madrone 20" dia., bears N.40°E., 33 lks. dist. with partially healed blaze, no marks visible.

A Madrone 38" dia., bears S.45°E., 44 lks. dist. with healed blaze. (Rec. 40 lks.)

A Madrone 18" dia., bears N.50°W., 19 lks. dist. with open decayed blaze.

and a bearing tree mkd. by Irving

A Chinquapin 14" dia., bears N.32°W., 26 lks. dist. with scribe marks T30S R4W S24 CS BT visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd:

T 30 S
R 4 W R 3 W
S 24 S 19
S 30
1983

Fd. OK, Aug. 1992 by R. Brown - M 115-56