


PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1435, surveyed April/May 1988 - (DCSO records Vol. 49 Page(s) 18647-48)

-----  
Point for the 1/4 sec. cor. of sec. 13 only, T30S R4W, at proportionate distance latitudinally on the E. bdy. of the section.

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.



from which

A Maple 19" dia., bears N.61°W., 44 lks. dist. mkd. 1/4 S13 BT.

A Madrone 22" dia., bears N.41°W., 106 lks. dist. mkd. 1/4 S13 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, and Robert H. Browning, Surveying Tech., under Group No. 2000, 2100, 2300 - Surveyed Aug. 2005 - (DCSO records Vol. 55 Pages 21619 & 21620 and 2009-1 A&B BLM Plat)

-----  
The 1/4 sec. cor. of sec. 13 only, monumented with a stainless steel post, 2 1/2" dia., firmly set, projecting 4" above ground, with brass cap mkd. as reported by Rogers in 1988; from which the remains of bearing trees mkd. by Rogers

A burnt maple stump, size indeterminate, bears N.61°W., 19.3 ft., no marks visible. (Record 29.0 ft.)

A roothole bears N.41°W. 70.0 ft. with fallen, burnt madrone trunk, size indeterminate, lying alongside, no marks visible.

and new accessories

A rebar, 30" long, 5/8" dia., driven 30" in the ground as a reference monument, bears S.61°W., 7.5 ft., with aluminum cap mkd. RM 1/4 S13 7.5 FT TO COR 2004, and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 30" in the ground as a reference monument, bears N.28°W., 7.5 ft., with aluminum cap mkd. RM T30S R4W 1/4 S13 7.5 FT TO COR 2004, and an arrow pointing to the cor.