

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 700566

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 7 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Robert Thompson - Feb/Apr. 1956 - C.S. File 42/173

-----  
Corner set by proportional measurement.

Set 1" Axle.

From which new trees:

8" D.Fir S.72°58'E., 32.8 ft.

14" Madrone S.2°10'W., 94.0 ft.

BLM survey by John Jelley, Cadastral Surveyor, under Group #599, surveyed Sept. 1965 - (DCSO records, Vol. 33 Page 13913)

-----  
Point for the ¼ sec. cor. of sec. 7 only, at proportionate distance in latitude.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

| T 30 S

| ¼ S 7

| R 3 W

1965

from which

A Fir 9" dia., bears N.67½°E., 27½ lks. dist. mkd. ¼ S7 BT.

A B.Oak 13" dia., bears South 4 lks. dist. mkd. ¼ S7 BT.

From this point, a point established by Robert Thompson in 1956, bears S.33°26'E., 0.82 chs. dist. monumented with an iron axle 1" dia., firmly set, extending 5" above ground, from which bearing trees mkd. by Thompson:

A Fir 12" dia., bears S.75½°E., 52 lks. dist. with healed double blaze.

A Madrone 14" dia., bears South, 143½ lks. dist. mkd. ¼ S7 3683 BT on double blaze.

Fd. BC & 2 BTs by David Edwards, 4/2007 - M152-75