

PRIMARY CORNER DESCRIPTION C.C. for Secs. 1 & 12 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. F. Briggs, Deputy Surveyor, under special instructions dated Aug. 7, 1891 0 (DCSO records Vol. 17 Page(s) 7104-05)

Set Dogwood post, 4½ ft. long, 4" sq., 24" in the ground, for cor. to secs. 1 and 12, T30S R4W, marked T30S R4W S1 CC on NW.; 1 notch on N. edge; S12 C C on SW.; 5 notches on S. edge, from which

- A R. Fir 16" dia., bears N.29°W., 21 lks. dist. mkd. T30S R4W S1 CC BT.
- A R. Fir 10" dia., bears S.80°W., 17 lks. dist. mkd. T30S R4W S12 CC BT.

Ben B. Irving - Deputy Co. Surveyor - Wit: Marion Perdue - July 22, 1927 - (See C.S. File 37/133)

Location identified from original BTs. Set 4"x6"x14" igneous rock 10" in ground. Remark original BTs.

BLM resurvey by John Jelley, Cadastral Surveyor, under Group #599, Surveyed Sept. 1965 - (DCSO records Vol. 33 Page(s) 13904)

The closing cor. of secs. 1 and 12, monumented with an iron pipe ¾" dia., firmly set, extending 4" above ground, from which the original bearing trees:

- A Fir 20" dia., bears S.80°W., 17 lks. dist. with healed blaze.
- A Fir 29" dia., bears N.29°W., 21 lks. dist., with scribe mark W visible on partly opened blaze on SE. face, and with scribe marks T30S visible on opened blaze on NE. face. The NE. face of this tree was marked by Wm. H. Byars in 1872. Briggs reported a Byars corner 25 lks. North of the closing corner of secs. 1 and 12, but did not describe it, and there is no other record of a Byars survey. I destroy the marks on the NE. face.

From the closing cor., a point established by Irving in 1928, bears N.30°E., 0.22 chs. dist., monumented with a basalt stone 14 x 8 x 6 ins., firmly set, extending 4" above ground, from which a bearing tree mkd by Byars in 1872:

- A Fir 18" dia., bears N.29°W., 17 lks. dist., mkd. S T30 R 4 W on opened blaze. I destroy the marks on this tree.

(Cont. Next Page)

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION C.C. for Secs. 1 & 12 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - A. Victor Cangie, Peter L. Earle, crew - March 31, 1976 - C.S. File 59/8-12

Found - Orig. 29" D.Fir which bears N.29°W., 14 ft. Visible scribing on previously opened SE. blaze, NE face had been cut out. Alive but damaged.

Orig. 20" now 24" D.Fir which bears S.80°W., 11 ft. Blaze healed over, tree alive and well.

3/4" x 17½" Iron pipe set at corner point.

At corner point determined by original BTs, I SET 1" x 30" Iron pipe with brass cap stamped: Douglas County Surveyor

T 30 S
R 4 W R W 3
S 1
S 12 S 7

Replaced found 3/4" Iron pipe in ground, North side of brass cap.

New BT - 10" Grand Fir bears N.71°W., 79.3 ft. mkd. "T30S R4W S1 CC CS BT" in a double blaze.

Fd. OK by David Edwards, 4/2007 - M152-75