

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 978010

PRIMARY CORNER DESCRIPTION Cor. No. 1 Therodore Lode MS 805

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____


Surveyed by C. Frank Rhodes, U.S. Deputy Mineral Surveyor -
F.T. Reynolds Mining Claim, know as the Therodore Lode,
South Umpqua Mining District, MS #805 - Feb. 15/16th 1919 -
(DCSO records Vol. 28 Page 12089)

Cor. No. 1
A fir post, 5 ft. long, 5" sq., set 2 ft. in the ground, in
mound of earth, scribed 1-805; whence
 A laurel, 7" dia., bears S.76°E., 37.2 ft and
 A fir, 5" dia., bears N.60°45'W., 8.5 ft.
Each blazed and scribed BT T 1-805
The NE cor. of sec 32, T30S R4W of the WM bears N.2°56'E.,
509.0 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral
Surveyor, under Group No. 2872, surveyed April 2017/Oct.
2019- (DCSO records Vol. 59 Page 23852-3)

Corner No. 1, Therodore Lode, restored by person(s) unknown;
from evidence no longer in existence; and is accepted as the
cor., monumented with an iron pipe, 1" dia., firmly set,
projecting 15" above ground.

At the corner point
Set a stainless steel post, 28" long, 2½" dia. 25" in the ground,
directly over the iron pipe, 48" long, with brass cap mkd.
T30S R4W



from which
 A fir, 5" dia., bears S.70½°E., 9.3 ft., mkd. X BT.
 A fir, 9" dia., bears S.31¼°W. 20.8 ft. mkd. MS805 TL-1 BT
From this cor 1 the cor. of secs. 28, 29, 32, and 33., bears
N.2°38'10"E., 509.88 ft. dist.