

TOWNSHIP 30 RANGE 04 POINT IDENTIFIER # 978020

PRIMARY CORNER DESCRIPTION Cor. No. 2 Therodore Lode MS 805

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____


Surveyed by C. Frank Rhodes, U.S. Deputy Mineral Surveyor - F.T. Reynolds Mining Claim, know as the Therodore Lode, South Umpqua Mining District, MS #805 - Feb. 15/16th 1919 - (DCSO records Vol. 28 Page 12089)

Cor. No. 2
A fir post, 4½ ft. long, 6" sq., set 2 ft. in the ground, in mound of earth, scribed T 2-805; whence
 A laurel, 8" dia., bears S.29°50'E., 25.5 ft., and
 A fir, 26" dia., bears N.17°20'W., 7.0 ft.,
Each blazed and scribed BT T 2-805

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23853-4)

Corner No. 2, Therodore Lode, restored by person(s) unknown; from original evidence no longer in existence; reported by Prochnau, (M21-33) in 1961; monumented with an iron pipe, 1" dia., firmly set, with top 12" below the surface of the ground (alongside of which is an iron pipe, 1" dia., 23" long, lying loose on the ground).

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 28" in the ground, directly over the iron pipe, 20" long, with brass cap mkd.
T30S R4W



from which
 A fir, 13" dia., bears S.54½°E., 45.5 ft., mkd. X BT.
 A fir, 9" dia., bears S.15¼°W., 23.1 ft., mkd. X BT.
Buried the other iron pipe, 23" long, alongside the stainless steel post.