

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S.

R 5 E

E
R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 71551

3. Malotte
R. Frost
Jackson County
Surveyors Off.
August, 1978
C.S. 58/183

Township corner common to Section 6; and Sec. 31 of T.29-5E; Sec. 1 of T.30-4E and sec. 36 of T.29-4E.

Found - projecting 8 ins., the 3 in. iron pipe with standard GLO brass cap properly marked as recorded by H.N. Raymond in 1929.

Orig. bearing tree, sawed fir stump shell, 36 ins. bears record N.32°E., 54.78 ft. to center.

Fir snag 26 ins. containing scribe mkd including "5E S6 BT" in partly exposed single face, bears S.80 1/2°E., 85.92 ft. to center (Rec. S.80 1/2°E., 85.14 ft.)

A white fir, 38 ins. with healed single blaze, bears S.81°W., 26.9' to center. (Rec. S.81°W., 28.38 ft.)

Shasta red fir, 41 ins. with healed single blaze. bears N.36°W., 25.9 ft. to center. (Rec. N.36°W., 27.06 ft.)

I mark new trees CS BT and take measurements to center of trees at lower blaze: White fir, 22 ins. bears N.16°E., 32.0 ft.

White fir, 10 ins. bears S.83°E., 64.78 ft.

Corner lies at north edge of marshy stream bed, 25 ft. south of south edge of clear cut and about 400 ft. west of location marker on 16 in. Fir alongside road. C N-S.

171
8/3/78