

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 047040

PRIMARY CORNER DESCRIPTION SE Cor. Briggs DLC #47

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set a post marked, from which
A B.Oak 8" dia., bears N.20°W., 67 lks.

E. Summers - Wit: Geo Bollenbaugh; S. Bollenbaugh - April 2,
1920 - Vol. 3 Pg. 68 and "old" Cor. Bk. Pg. 147

Reset from old BT. Set stone from which new BTs bear as
follows:
A Laurel 8" dia., bears S.81°00'W., 24 lks.
A W.Oak 22" dia., bears S.00°00'W., 12 lks.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike
Darby; Jim Halterman - Oct/Nov. 1963 - C.S. file 53/26-33

Found - Stone at corner and both BTs as described by
Summers. SW BT shows scribing.
Fence corner to West and North bears N.20°W., 6.0'.
Set Brass cap alongside cor. stone, mkd: County Surveyor's
Office 1963, S.E. DLC 47 T30S R5W.
New BTs -Rescribe, now 24" W.Oak, South, 7.9 ft. SE DLC 47
CS BT.
Rescribe, now 20" Laurel S.81°W., 15.9 ft. SE DLC 47
CS BT.

Fd. OK, Jan. 1992, R. Dolan, M 114-37
Found OK by R. Brown, Sept. 2002 - M141-1
FD. Ok by R. Brown, 12/2008 - M157-7

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- Feb. 13, 2013 - C.S. File 67/38-19

Found - A stone measuring 5x3" protrudes 2" above ground,
stone shows no marks. 1920
A 2½" dia., brass cap (properly mkd) on a 1" I.D.
iron pipe is firmly and plumbly set, protruding
18" above ground, on the east edge of the above
fd. stone. 1963
Accessories measured from fd. BC
A B.Oak 8" dia., now a 26" dia., B.Oak with the
center 20+" rotted away (no blaze or scribing
evidence fd); bears N.22½°W., 44.2 ft. (rec.
N.20°W., 44.3 ft.) OBT

continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 047040

PRIMARY CORNER DESCRIPTION SE Cor. Briggs DLC #47

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A laurel 8" dia., now a 29" dia., madrone with a fully healed double blaze; bears S.81°W., 15.8 ft. (as per rec.) 1920
A W.Oak 22" dia., now a 25" dia., W.Oak with an exposed double blaze with faces rotted away; bears South, 7.9 ft. (as per rec) 1920
New - BC/IP monument position is referenced out and monument is removed from ground, monument is replaced at referenced position and now protrudes 7" above ground on east edge of fd. stone.
A 9" dia., D.Fir scribed "SE DLC 47 CS" "BT" on a double blaze; bears N.27½°E., 16.3 ft.
A 6" dia., I.Cedar scribed "X" "CS BT" on a double blaze; bears N.48½°W., 7.7 ft.
Note - Monument is on moderate east slope in mixed open woods of fir, cedar, oak and madrone.
Compass decl. 15½°E.