

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 050020

PRIMARY CORNER DESCRIPTION WC NW Cor. Colvig DLC #50

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set a post marked, from which
A B.Oak 15" dia., bears S.50°E., 41 lks.

E. Summers - For: Bollenbaugh Estate - April 2, 1920 - Vol.
3 Pg. 68

Reset from field notes. Set stone 255 lks. South of true
corner which is in S. Umpqua River, from which
An Alder 4" dia., bears S.80°W., 82 lks.
An Alder 8" dia., bears N.77°30'E., 179 lks.

Raymond Brown, L.S. #2391 - For: Lois M. Clough - April 1990
M 101-78

Set - 2" x 36" I.Pipe with brass cap attached mkd. "L.S.
2391, WC, T30S R5W NW Cor., DLC 50 1990" (per
map, 154.32 ft.)

Accessories:

Power Pole (Plate #PPL 30-05 214501) bears S.51°W.,
14.0 ft. to center.

18" English Walnut bears S.42°50'E., 22.8 ft. mkd. "X
BT"

3/4" I.Rod (State Hwy R/W Station 429+00) bears
S.71°12'30"E., 134.0 ft.

Center line Co.Rd. #1 bears S.0°43'15"W., 63.7 ft.

Water's edge of the So. Umpqua River bears
N.0°43'15"E., 112.0 ft.

Point for the NW Cor.DLC #50 falls in the So. Umpqua River.
Unable to set.

Fd. W.C. OK, Jan. 1992, R. Dolan, M 114-37

FD. Ok by R. Brown, 12/2008 - M157-7