

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 050040

PRIMARY CORNER DESCRIPTION SE Cor. Covig DLC #50

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original DLC survey by Bowman and Burnett under Contract date Sept. 24, 1855

Set post in west line of Claim No. 51 marked as per instructions, from which
A B.Oak 10" dia., bears N.27°W., 14 lks.

Briggs - For: Bollenbaugh - 1892 - Vol. 1 Pg. 214; Field Book 4 Pages 31-32

Set Post, from which
A W.Oak 8", N.44°W., 26 lks.

E. Summers - For Bollenbaugh Estate - April 1920 - Vol. 3 Pg. 68 and "old" Cor. Bk. Page 147

Reset from old BT. Set stone from which new BTs bear as follows:
A Laurel 10" dia., bears N.58°00'E., 5 lks.
A Laurel 6" dia., bears N.84°00'W., 13 lks.

John H. Markham Jr. - For: Canyon Logging Co. - June 14, 1955 - C.S. File 42/19

Determined by O.B.T.
At corner point, Set 1" x 30" Iron pipe, from which
17" B.Oak windfall, bears N.27°W., 9.2 ft. O.B.T.
6" Laurel bears N.75°W., 8.5 ft. found scribe. O.B.T.
16" Laurel bears N.46°E., 3.5 ft. O.B.T. I rescribe Cl 50
10" Cedar bears S.36°E., 8.1 ft. mkd. DLC 50 BT.
Fence corner bears N.72°E., 8.0 ft., fences running N-S-W.
1/4 Cor. to Sec. 27 and 28 bears North 377.0 ft.

George J. Wenderoth - John Meyer - May 26, 1966 - M 31-62

Set Brass cap, from which
10" Laurel N.75°W., 8.5 ft.
14" Cedar S.36°E., 8.1 ft.

Found OK by R. Brown, Sept. 2002 - M141-1

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Jan. 18, 2013 - C.S. File 67/38-9

Found - No evidence of 1920 stone or 1955 IP fd.
A 2½" dia., brass cap mkd: "COUNTY SURVEYORS OFFICE SE COR + DLC 50 LS 5" is firmly and plumbly set protruding 9" above ground. continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 050040

PRIMARY CORNER DESCRIPTION SE Cor. Covig DLC #50

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A B.Oak, 10" dia., now a well defined root-hole with rotted oak remains (too low for blaze evidence) bears N.27°W., 9.2 ft. (as per rec.) OBT
No evidence of 1892 renewal BT remains.
A laurel 10" dia., now a 17" dia., madrone with a fully healed single blaze; bears N.51°E., 4.0 ft. (rec. N.58°E., 3.3 ft. is a reasonable face measurement) 1920
A laurel 6" dia., now a 10" dia., madrone, not showing a visible blaze; bears N.75°W., 9.3 ft. (bearing agrees with 1955 rec., distance record maybe to face of tree) 1920
A 10" cedar now a 21" dia., I.Cedar with a fully healed double blaze; bears S.40½°E., 8.1 ft. (rec. S.36°E., 8.1 ft.) 1955
Previously noted N-S fence mostly gone some standing fence runs west from NE BT.
New - An 11" dia., D.Fir scribed "SE DLC 50 CS" "BT" on a double blaze; bears N.38½°W., 21.0 ft.
Note - Monument is on land sloping moderately east & south and is just east and south of a flat ridge top. Land is forested with oak, madrone, fir and cedar.
Compass decl. 15½°E.

Fd as per rec. by N. Hibbs - June 2018 - M171-45