

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 051040

PRIMARY CORNER DESCRIPTION S SE Cor. Clark DLC #51

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original DLC survey by Bowman and Burnett under Contract date
Sept. 24, 1855

Set a post in bottom prairie marked, from which
A Yellow wood 6" dia., bears N.80°W., 616 lks.

George J. Wenderoth, deputy Co. Surveyor - Frank Loso;
Charles Leiser - May 1949 - C.S. File 40/270

Set from measurement from SW Cor. and Interior L Corner.
Drive 1" Iron Pipe for corner.
Scribe - 10" Twin W.Oak N.55°E., 183.0 ft.
12" Maple N.85°15'E., 109.9 ft.

Douglas Co. Surveyors Office - Crew - Stephen J Flaue &
Mike Koch - 10/29/2012 (filed 3/16/2020) - C.S. File 67/46-10

Found - A 1" dia. iron pipe by Wenderoth, in 1949, firmly
set, 6" below the ground & 2 ft. south of
East-West fenceline.

BTs by Wenderoth -

A root hole bears N.55°E., 183.0 ft. (10" W.Oak per
record).

A 24" Maple bears N.85°15'E., 109.9 ft. with healed
double blaze

New - A 1¼" Drill rod per M7-70 with mushroomed top 1"
below the ground bears S.19°14'W., 240.5 ft.
(Rec. 240.8 ft.)

A 1"x2½" BCIP at the NW corner of DLC 58 bears,
S.89°41'W., 82.6 ft.

A 41" Sequoia bears N.53¼°W., 90.0 ft. (not blazed
or scribed because it has a sign on its West side
marked "Ed Hyatt Memorial")

Note - Basis of Bearings: S.89°41'W., 82.6 ft. between the
NE Corner of DLC 58 and the SSE Corner of DLC 51
per M7-70

All BTs have BT tags attached.

1949 monument is found on flat land in with mixed
timber.

Compass decl. 15°E.