

PRIMARY CORNER DESCRIPTION SE Cor T Smith DLC #55

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original DLC survey by Bowman and Burnett under Contract date Sept. 1855

Set a post marked, from which
An Ash 12" dia., bears N.80°W., 102 lks.

J.H. Markham, Jr. - For: Markham - Wit: Combs - Nov. 6, 1952
C.S. File 41/80

Determined by O.B.T., an Ash stump bears N.80°W., 67.0 ft.
At corner point, Set ¼" x 30" Iron pipe, from which
10" W.Oak bears N.78°W., 47.0 ft. mkd. D.L.C. 55 BT.
33" B.Oak bears N.52°W., 81.0 ft. mkd. D.L.C. 55 BT.
The East ¼ cor. sec. 24 bears South, 200.0 ft. The corner lies on the North edge of the C.O.P. Co. R/W in open field. Section corner lies North, 2470 ft.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 12-2-2004 - C.S. File 67/6-30

Found - 1/2"x30" iron pipe flush with top of ground.
10" W.Oak, now possible depression near rec. brg. & dist.
33" B.Oak, now fallen 30" dia., fallen B.Oak out of position. Root hole bears N.52°W., 81.0 ft.

Set - 2½" BC on 1¼"x30" IP was set at referenced position of Markham's 1/2" IP, protrudes 5". 1/2" IP was reset at Northerly edge of BC/IP. MKD:

DOUGLAS CO SURVEYORS OFFICE
T 30 S
R 5 W
|
SE DLC 55
2004

11" Maple, double blazed & scribed "SE DLC 55 CS BT" bears N.47½°W., 105.5 ft. (Tree leans Northerly)
Double trunk W.Oak double blazed & scribed "SE DLC 55 CS BT" bearing & dist. to center root crown of double trunk bears S.77°W., 51.2 ft. scribed on 12" D.B.H. southerly trunk.
NW leg of power line trestle bears S.64½°E., 95.1 ft
West ¼ cor. sec. 24 T30S R5W (DCSO BC/IP) bears S.2¼°W., 198.1 ft. (Rec. South - 198.0 ft. GLO)

Note - Corner lies near edge of open field 22 ft. ± East of N-S fence line.
Decl. 17¼° E.