

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 and 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7131)

Set a post cor. to secs. 25, 30, 31 and 36, from which
A B.Oak 15" dia., bears N.42°E., 97 lks. dist.
A B.Oak 20" dia., bears S.80°E., 85 lks. dist.
A B.Oak 6" dia., bears N.7°W., 47 lks. dist.
A B.Oak 5" dia., bears S.85°W., 61 lks. dist.

Doug. County Surveyors Office - George Wenderoth, Deputy -
Witness: R.C. Head; R.F. Pfaff - Oct. 1946 - C.S. File
44/151; M 20-24

Drive 1" Pipe for corner.
Find both old BTs, badly rotted, mark new BTs:
A 10" Fir N.29°00'E., 61.4 ft.
A 16" Fir S.72°22'E., 13.8 ft.

Doug. County Surveyors Office - James Byron, Deputy - Mike
Darby; Jim Halterman - Nov. 1963 - C.S. File 53/26-31

Found - 1" I.Pipe at corner.
10" Fir N.29°E., 61.4 ft., OK.
SE BT now stump.
New BT - 16" R.Fir bears S.6°E., 24.2 ft. scribed T30S R5W
S31 CS BT.

Doug. County Surveyors Office - R.B. Kimberling; F.C. Silagy;
P.L. Earle - April 13, 1978 - C.S. File 59/46-21

Found - 1" x 44" I.P. set 32" in the ground.
15" orig. now 42" remains of stump at ground level
bears N.44½°E., 62.2 ft. (Rec. N.42°E., 64.0 ft.)
Stump hole bears approx. S.80°E., 55.0 ft. (Rec.
56.1 ft.)
6" now 18" B.Oak is down, orig. position approx.
bears N.7°W., 31.0 ft. I chop open well healed
blaze to find scribing has been chopped out.
5" now 15" B.Oak bears S.88°W., 42.6 ft. @22°=39.5
ft. (Rec. S.85°W., 40.3 ft. with a badly rotted
blaze apparently chopped out.
10" now 20" Fir stump 5 ft. high, bears N.31°E.,
(Rec. N.29°E.) 61.4 ft. with visible scribing
"S30 CC" in a partly healed double blaze.
16" now 18" Fir stump bears S.72°22'E., 13.8 ft.
with a rotted out blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" now 18" D.Fir bears S.3½°E., (Rec. S.6°E.) 24.2 ft. with a double well healed blaze.

Set a 1" x 36" I.P. with a brass cap set at ground level and marked: Douglas County Surveyor T 30 S

R	S 36		S 30	R
6			S 31	5
W			1978	W

New BTs -6" D.Fir bears N.41°E., 20.1 ft. I double blaze and scribe "T39S R5W S30 CS BT".

7" D.Fir bears S.16°E., 6.7 ft. I double blaze and scribe "T30S R5W S31 CS BT".

Cor. is 6 ft. East of a N-S wire fence, 125 ft. East of a dirt road West of small creek.

Found OK by B. Rogers, Oct. 1996 - 1996-0100

DCSO-GIS Corner visitation - 2/2/2005 - Typed: 2/2/2011 - C.S. File 67/33-1

Monument - BC/IP - 2¼" BC on 1¼" IP
Comment - OK

Fd. ok by D. Beedle, 10/2007 M154-52