

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100443

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 13 only, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7196)

-----  
Set quarter sec. post around which a  
B.Oak 17" dia., bears N.3°E., 47 lks.  
B.Oak 18" dia., bears S.48°W., 90 lks.

George Wenderoth, Deputy Co. Surveyor - C.L. Morley - April 1946 - C.S. File 38/244 For: G.D. Shake & F.E. Weaver

-----  
Old BT, 26" W.Oak S.48°W., 59.4 ft., uprooted.  
Drive 3/4" Iron pipe and marked BTs:  
26" B.Oak N.14°15'E., 22.0 ft.  
23" W.Oak S.88°20'W., 116.9 ft.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Sept. 19, 2013 - C.S. File 67/40-8

-----  
Found - The 1946 corner monument: A 3/4" iron pipe now a 3/4" I.D. iron pipe set plumb protruding 3" above ground.

Possible evidence of one OBT: A B.Oak 18" dia., now a shallow root-hole depression; bears S.48°W., 59.4 ft. (M/L) as per rec.

A 26" B.Oak now a 36" dia., B.Oak with a fully healed single blaze; bears N.14¼°E., 22.0 ft. (as per rec.) 1946

A 23" W.Oak now a 27" dia., W.Oak with a partly healed single blaze (Bees inside, do not check for scribing) bears S.88¼°W., 118.0 ft. (rec. S.88°20'W., 116.9 ft.) 1946

New - A 33" dia., W.Oak scribed "¼ S13" "CSBT" on a double blaze; bears S.75¾°E., 75.5 ft.

A 20" dia., W.Oak scribed "¼ S13 CS" "BT" on a double blaze; bears N.22¼°W., 61.0 ft.

Note - Monument is on top of high ridge in open pasture land with scattered oak and madrone.  
Compass decl. 15½°E.

Fd. ¾" IP 8/2021 by R. Badgley - M178-40