

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100504

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7196)

Set post cor. to secs. 12, 13, 7 and 18, from which
A B.Oak 24" dia., bears S.38°W., 102 lks.
A B.Oak 24" dia., bears S.58°E., 7 lks.
A B.Oak 26" dia., bears N.71°E., 58 lks.
An Ash 10" dia., bears N.73°W., 95 lks.

Ben B. Irving, Deputy, Douglas Co. Surveyor - Wit: L.H. Smick; N.E. Richardson; Allen Moore - April/May 1929 - M 1-61; C.S. File 1/65 A and B; "old" cor. Bk. Page 183

NOTE: The records of corner descriptions of the Public Survey Office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and Co. Surveyor, and in view of the fact that no corners in field checked records and that age of corners corresponded with original work, it was decided to use field corners as the true corner and they were renewed accordingly.

Reset from one O.B.T. and stump of another. A 1" x 48" Galv. I.Pipe driven 14" under ground in Prune orchard, from which
An Ash 30" dia., bears N.73°W., 102 lks. (Orig.) which I rescribed T30S R6W S12 CS BT.
W.Oak 6" dia., bears S.51°W., 75 lks. blazed and scribed T30S R6W S13 CS BT.
A Prune 8" dia., bears S.76°E., 2 lks. blazed and scribed T30S R5W S18 CS BT.
A Maple 14" dia., bears N.57½°E., 326 lks. blazed and scribed T30S R5W S7 CS BT.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-22

Found - 1" I.P. 15" under surface at corner.
Both BTs as recorded by B. Irving. (also see M20-23)
6" now 18" B.Oak, (stool) shows scar. We rescribe S13 T30S R6W CS BT., bears S.80½°W., 38.1 ft.
Set 3/4" Iron rod alongside I.P. and 3" above surface.

Douglas Co. Surveyors Office - Stephen J. Flaue - John Pike - 2/10/2005 - C.S. File 67/10-9

Found - 1" I.D. iron pipe 15" under ground. 5/8" I.R. alongside leans Northerly 0.4 ft. & is approx. 2" under ground. continued next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100504

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T30-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

14" Maple now split, partially fallen partially rotted, multi-trunk Maple, rec. brg. & dist. to apparent center of southerly once separate group of trunks. Center of root crown bears N.56 $\frac{3}{4}$ °E., 213.7 ft. B. Irving rec. N.57 $\frac{1}{2}$ °E., 215.2 ft. (May 1929)

18" B.Oak now 16" healed blaze visible bears S.2 $\frac{1}{4}$ °W., 171.3 ft. (Rec. S.3°27'W., 168.4 ft. per M20-23. This tree now also witnesses the SSE cor. of DLC 37.

New BTs- 5/8" I.R. w/yellow plastic cap mkd: "R.BROWN PLS 2391" bears N.9 $\frac{3}{4}$ °W., 223.0 ft. (At fence corner running West & North)

Triple trunk Ash, most Easterly trunk is 15" dia. is double blazed and scribed "T30S R6W S13 CS BT" bears S.44°W., 36.3 ft. to center root crown.

28" dia., English walnut double blazed & scribed "X BT" bears N.50 $\frac{1}{2}$ °E., 64.1 ft.

Note - Corner lies in pasture.
Comp. decl. 17 $\frac{1}{2}$ °E.

Fd. BC by G. Lang, 5/2011 - M162-47