

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, of T30-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7189)

-
- Set post, cor. to secs. 6, 7, 1 and 12, from which
- A Pine 36" dia., bears N.45°W., 12 lks.
 - A Laurel 20" dia., bears S.3°W., 63 lks.
 - A Laurel 22" dia., bears S.87°E., 123 lks.
 - A Laurel 25" dia., bears N.45°E., 104 lks.

Doug. County Surveyors Office - Ben B. Irving, Deputy - Wit: L.H. Smick; N.E. Richardson - April/May 1929 - M 1-61; C.S. File 1/65 A & B; and "old" cor. Bk. Page 183

NOTE: the records of corner descriptions of the Public Survey office at Portland does not agree with corners as found on ground. Remainder of field notes check reasonably close. After consultation with Dist. Attorney and County Surveyor, and in view of the fact that no corners in field checked records and that age of corners corresponded with orig. work, it was decided to use field corners as the true corner and they were renewed accordingly.

Location of this corner identified from one O.B.T. and position of Sec. cor. 6 and 7 on range line.

Drove 1" x 18" shaft 26" underground from which

- A W.Oak 6" dia., bears S.59°46'W., 160 lks. blazed and scribed S12 T30S R6W CS BT.

Stump of O.B.T. as recorded.

Section corner betw. 6 and 7, T30S R5W bears S.0°51'E., 3.98 chs.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-24

Found - 1¼" Axle at corner 24" under surface.
No trace of BT. Checks bearing and dist. from cor. to secs. 6 and 7, N.1°W., 262.7 ft.

Set 3/4" Iron rod alongside Axle and 12" under.

New BTs -8" W.Oak bears S.59°W., 143.6 ft. scribed S12 T30S R6W CS BT.

12" B.Oak bears N.65°W., 106.8 ft. scribed S1 T30S R6W CS BT.

Set 3/4" I.R. under field fence, N.65°W., 49.6 ft.

Doug. Co. Surveyors Office - L.E. Monrean, Deputy - K. Reed; P.Earle; T.Plouff - Oct. 2 & 4, 1979 - C.S. File 60/34-16

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T30-6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Found - A 3/4" I.Rod buried 18" under ground.
An 8" W.Oak now 12" with well healed double blaze bears S.59°W., 143.6 ft.
A 12" B.Oak now 14" with partially healed double blaze bears N.65°W., 106.8 ft.
A 3/4" I.Rod 18" above ground, 1.5 ft. north of RR R/W fence bears N.65°W., 49.6 ft. We drive rod 10" farther into ground.

New Accessories:

A 1½" x 1½" x 48" angle iron post set 24" in ground bears West, 59.9 ft. Post in RR R/W fence.
2" high letters "X BO" chiseled on face of easterly culvert headwall under SP tracks, "X" is 0.65 ft. below top of 7.5 ft. long headwall, bears N.34°W., 144.9 ft.

Corner in large plowed field.

Accessories found, June 8, 1984 by DCSO, C.S. File 62/18-28

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1551, Surveyed Aug/ 1990/July 1991 - (DCSO records Vol. 50 Page(s) 19199-200)

The cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., perpetuated by Irving, in 1929, from original evidence no longer in existence, further perpetuated by Byron, in 1963, and further perpetuated by L. E. Monrean of the County Surveyors Office in 1979, monumented with an iron rod, 1½ ins. diam., firmly set 30 ins. below the ground surface, with an iron rod, 3/4 in. diam., set 24 ins. below the ground surface, alongside, from which a bearing tree and reference monument mkd. by Byron:

An oak, 14 ins. diam., bears S. 58½° W., 215½ lks. dist., with healed double blaze.

An iron rod, 3/4 in. diam., projecting 12 ins. above the ground, bears N. 66° W., 75½ lks. dist.

and a reference monument and bearing object mkd. by Monrean

An angle iron, 1½ x 1½ ins., projecting 12 ins. above ground, bears S. 88° W., 90½ lks. dist.

The mark X with marks BO alongside, in a concrete headwall, bears N. 34½° W., 219 lks. dist.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, flush with the surface and directly over the iron rods, with brass cap mkd:

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100604

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T30-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T30S	
R6W	R5W
S 1	S6
S12	
1991	

Fd. Ok by Kris DeGroot - 06/2001 - 2001-0061