

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION N.W. Cor. Sec. 6 (NW Tsp cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6422)

-----  
Set a post for cor. to secs. 1, 6, 31, & 36 for cor. to tps. 29 & 30, South, Rgs. 5 & 6 West, from which a -  
Pine, 15" dia., bears N.15°E., 98 lks.  
Pine, 5" dia., bears N.55°W., 18 lks.  
Pine, 5" dia., bears S.45°W., 30 lks.  
Pine, 6" dia., bears S.40°E., 17 lks.

-----  
Doug. County Surveyors Office - Ben B. Irving, Deputy Co. Surveyor - Witnesses: H.C. Baird, Weaver - C.S. File # 1/65B; Field Notes Page 80 - Vol. 3 Pg. 294 - M 1-61.

-----  
Location identified by an East & West blazed line and distance from Rocky ridge S. & N. called for in original notes. Drove 3/4"x36" gal. Iron Pipe and set in a mound of rock from which a  
Pine, 20" dia., bears S.37½°E., 98 lks. blazed and scribed T30S R5W S6 CSBT.  
Pine, 16" dia., bears N.63°E., 52 lks. blazed and scribed T29S R5W S31 CSBT.  
Pine, 16" dia., bears S.32°W., 123 lks. blazed and scribed T30S R6W S1 CSBT.  
Pine, 20" dia., bears N.65°W., 82 lks. blazed and scribed T29S R6W S36 CSBT.

-----  
Howard Johnstone - For: Roseburg Lumber Co. - April 1978 - RM 3-12.

-----  
Found - 3/4" I.P. and 4 BT's (all down)  
Set - 5/8"x30" Iron Rod and alum. cap in I.P.  
New BTs -6" Pine, N.4½°W., 50.0'.  
8" Pine, N.67°E., 3.6'.  
12" Pine, S.85°W., 31.3'.  
8" Pine, S.29°E., 41.3'.

-----  
Douglas Co. Surveyors Office - Stephen J. Flauser - John Pike - 3/15/2004 - C.S. File 67/6-4

-----  
Found - 5/8" rebar/alum. cap.  
OK