

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

G.G. Stewart, Deputy - For: J.M. Yocum; Edwin Weaver - Dec. 16, 1921 - Vol. 3 Pg. 105; C.S. File 7/14

I set the approximate center of section

Drove I.P. for corner and mkd.
A 24" Pine, bearing S.79°E., 75 ft.
An 8" W.Oak bears N.78°E., 103 ft.

Floyd Frear, Surveyor - Andy Andrews; Leo Kershner; Glen Baughman, Witnesses. - June 29, 1950 - C.S. File 40/258

I find iron pin gone.
Reset 3/4" x 36" Iron bolt, from which
Old Oak BT, N.68½°E., 103 ft. (was N.78°E.)
Pine BT, S.79°E., 75 ft., OK.

George E. Grubb, - For: Milton Herbert - March 1981 - M 87-22

Proportioned C 1/4 but nothing set.
Found 3/4" steel rod bears N.88°54'E., 34.10 ft. from true corner.

Found Alum. cap by W. Rogers, Nov. 2001 - M139-7.

DCSO-GIS Corner visitation - 2/28/2005 - Typed: 2/7/2011 - C.S. File 67/33-1

Monument -
Comment - (needs) rehab

Neil Hibbs - For: Lynn Herbert - 6/2014 - M168-17

Found - Orig. oak BT to Ne is still there. Still has tag referencing point "A" (3/4" bolt that bears N.88°32'42"W., 34.10' from C¼ cor.)
Set - 5/8"x30" iron rod w/cap stamped "HIBBS-LS 52989"
Reference monument: A 5/8"x30" iron rod w/cap stamped "HIBBS-LS 52989" bears N.2°15'37"E., 153.50'