

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7156)

Set ¼ sec. post at average distance, from which
A W.Oak 15" dia., bears N.42°E., 50 lks. dist.
A B.Oak 8" dia., bears S.25°W., 30 lks. dist.

G. G. Stewart - Set in presence of Vernon Weaver; Bill Weaver; J.M. Yocum; M. Jones - Dec. 29, 1921 - C.S. File 7/14; Vol. 3 Page 105

Put in I. Pipe. Marked new BT. Making position of ¼ cor. for 18 and 19 as N.89°04'E., 2950.9 from sec. cor. 13, 18, 19 and 24.
BTs - 18" B.Oak N.84°E., 6.6 ft.
10" Laurel S.36°W., 38.0 ft.

B.B. Irving - For: Fitzpatrick - April/May 1948 - M 20-23

Found 1" I.P. and old BT.
18" Fir marked ¼ S S0°32'W., 7.6 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darbey; Jim Halterman - Oct. 1963 - C.S. File 53/26-26

Found - 1" I.P. at corner and under E-W fence.
Now 20" Fir S.0°30'W., 7.6 ft. shows scribing on old face.
Do not find any trace of original BTs.

New BT - 5" W.Oak bears N.29°E., scribed ¼ S18 CS BT, scribed high.

We find BTs for another corner thus: From a point that bears N.12°W., 61 ft. from 1" I.P. at ¼ corner, these BTs bear from that point:

12" Laurel South 26.5 ft. shows old scribing.
16" W.Oak N.80°E., 30.5 ft. shows scribing 50 yrs. old.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15556)

Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.

(Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 3 ft. base, to top, with brass cap mkd: T 30 S R 5 W

¼ S 18
S 19
1969

from which

A Madrone 15" dia., bears N.68°W., 72 lks. dist., mkd. ¼ S18 BT.

A Ponderosa Pine 6" dia., bears S.4°E., 48 lks. dist., mkd. ¼ S19 BT.

From this point, an iron pipe, 1" dia., firmly set, projecting 3" above ground, bears S.41°12'E., 2.25 chs. dist., origin unknown.

Cor. Fd. OK, J.H. Markham, Jr., May 24, 1982 - M 92-33
Cor. Fd. OK, R. Brown, Sept. 1992, M 115-69

DCSO-GIS Corner visitation - 2/28/2005 - Typed: 2/7/2011 -
C.S. File 67/33-1

Monument - 3" BC/IP
Comment - (needs) rehab