

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7157)

Set ¼ sec. post, at average distance, from which
A B.Oak 15" dia., bears N.55°W., 33 lks.
A B.Oak 18" dia., bears S.75°E., 53 lks.

Doug. County Surveyors Office - N.E. Richardson, Deputy -
Wit: Evans - May 1948 - C.S. File 39/171; M 20-23

Set 1" x 36" I.P. with brass cap 2 ft. underground, mkd:
County Surveyors Office ¼ Cor. S 7
S 18

Marked BTs: 12" Oak N.56°W., 24.3 ft. mkd. ¼ S7 CS BT.
24" Oak S.35°E., 72.0 ft. mkd. ¼ S18 CS BT.

Doug. County Surveyors Office - James Byron, Deputy - Mike
Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-23

Found - Brass cap at cor., 8" under surface.
12" now 14" W.Oak N.56°W., 24.3 ft., shows good
scar.
SE BT not found.

New BTs -12" W.Oak bears S.25°W. 124.5 ft scribed ¼ S18 CS BT
14" W.Oak bears N.62°W., 35.7 ft. scribed ¼ S7 CS BT

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 6/14/2005 - C.S. File 67/10-30

Found - 2½" dia., brass cap with illegible markings 9" below
ground.
14" now 24" dia., W.Oak, fully healed double blaze
visible bears N.57½°W., 24.3 ft. (rec. N.56°W.,
24.3 ft.) 1948 BT.
12" now 20" dia., W.Oak, fully healed double blaze
visible bears S.25°W., 124.5 ft. (agrees w/rec)
1963 BT

New - Center of 8" dia., fiberglass Doric Column at the SW
corner of House bears N.53°E., 160.1 ft.
24" dia., B.Oak, double blazed & scribed "¼ S18 CS
BT" bears S.29½°E., 168.2 ft.

Note - Corner lies in lawn area with gravel roads on West,
South & East sides. Auto Body shop is close by.
Comp. decl. 16¾°E.