

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & 31 T.29-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Pages 6425 & 6426)

-----  
Set a post at proper distance for 1/4 sec. cor., from which  
A B. Oak, 12" dia., bears S.85°E., 30 lks.  
A W. Oak, 20" dia., bears N.83°W., 12 lks.

M. B. Germond Co. Surveyor - Witnesses: Ed Weaver, Cleal Weaver, Hank Weaver, Joe Weaver, F.C. Frear, John Dicks, Harry Strong, Chris Christesen - Mar/Sept. 1917 - C.S. File # 7/9 - F.B. 42 Pg 29 - C.S. File # 54/108 - M 1-35.

-----  
I renew this corner from one old BT as follows:  
1/2"x48" gal. Iron Pipe from which,  
A W. Oak, 20" dia., bears N.40°30'E., 96 lks.  
A W. Oak, 16" dia., bears S.72°30'E., 50 3/4 lks.

William J. Ruppert, L.S. # 866 - For: Darrel Green - May 1980 - M 83-65 A&B.

-----  
Found - 1/2"x48" Iron Pipe  
36" W.Oak bears N.40°30'E. 63.5' good scar now dead.  
30" W. Oak, bears S.72°16'E., 33.5'.  
Set - A 1"x30" gal. iron pipe with 2 1/2" brass cap at position of 1/2" pipe. Stamped brass cap:  
T29S | S31 1/4 R5W PLS 866 1980  
T30S | S6  
Replaced 1/2" pipe alone east side of Brass cap.  
New BT - 16" W. Oak, bears N.44°50'W., 95.65' scribed 1/4 S31  
BT. Attached brass washer LS 866 to lower blaze.

Fd. Brass cap, Sept. 1991, Raymond Brown, Partition plat 1991-0071

Fd. Brass cap, Nov. 2003 by N. Hibbs see M143-41