

PRIMARY CORNER DESCRIPTION S.E. 1/16 Cor. Sec. 31

Alias	Description

Doug. County Surveyors Office - Gary Langitz; Ed Monrean; Karen Reed; F. Silagy; Vicki Woodral; P. Earle - July 16, 1979 - C.S. File 61/3; RM 3-26

At position of SE 1/16 corner Sec. 31 as determined by survey:

We Set a 1" x 36" I.P. 34" into the ground with attached brass cap stamped: "Douglas County Surveyor T30S R5W SE 1/16 + S31 1979".

New BTs -9" D.Fir scribed "SE 1/16 S31 CS BT" on a double blaze bears N.59°E., 27.0 ft.

16" Maple scribed "SE 1/16 31 CS BT" on a double blaze bears S.10°E., 85.7 ft. This tree located in creek bottom running northerly.

Fd. OK, July 1990, M 112-4

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 1/30/2007 - C.S. File 67/21-4 & M146-53

Found - 2½" dia., brass cap (properly) marked as shown projects 3" above ground.

9" now 17" dia., D.Fir, fully healed double blazed found as per 1979 record.

16" now 16" dia., Maple, fully healed double blazed found as per 1979 record.

Set - 2½" dia., brass cap on 1¼" O.D.x30" iron pipe. Projects 8" above ground.

1979 brass cap is cut off and now becomes an accessory for new position. BT tags removed from 1979 BTs

BC mkd: DOUGLAS CO SURVEYORS OFFICE

T30S

R5W

SE + 1/16

S 31

2007

10" dia., B.Oak double blazed & scribed "SE 1/16 S31 CS BT" bears N.38°W., 20.5 ft.

7" dia., Madrone double blazed & scribed "SE 1/16 S31 CS BT" bears N.63½°E., 23.3 ft.

1¼" O.D. iron pipe, projects 1" above ground, bears N.74°50'26"W., 222.30 ft.

Note - Lies on gentle North East facing slope approx. 66 ft. West of old N-S fence line.

Compass decl. 16¼°E.