

PRIMARY CORNER DESCRIPTION CE 1/16 Sec. 31

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Doug. County Surveyors Office - Gary Langlitz; L.E. Monrean; Karen Reed; P. Earle; Vicki Woodral; F. Silagy - July 17, 1979 - C.S. File 61/3; RM 3-26

Set - At position of center east on 1/16 cor. Sec. 31 as determined by survey, We Set an I.P. 1" x 36" with brass cap attached flush with ground. Cap is stamped "Douglas County Surveyor T30S R5W C E 1/16 C S31 1979". Set witness post and sign 2 ft. south.

New BTs -11" D.Fir scribed "CE 1/16 S31 CS BT" on a double blaze bears S.77 3/4°E., 209.6 ft.

20" W.Oak blazed and scribed "CE 1/16 S31 CS BT" bears S.35°E., 67.2 ft.

Monument is approx. 187 ft. West of a N-S fence.

Fd. OK, July 1990, M 112-4

Douglas Co. Surveyors Office - Stephen J. Flaue - John Pike - 1/10/2007 - C.S. File 67/21-16 & M146-53

Found - 2½" dia., DCSO brass cap flush w/ground. (1979)
11" now 20" dia., pistol butt D.fir, fully healed double blaze, fd as per 1979 rec.
20" now 27" dia., W.Oak, fully healed double blaze, fd as per 1979 rec.

New - 2½" dia., brass cap on 1¼" O.D.x30" long iron pipe projects 7" above ground. BC mkd:
DOUGLAS CO SURVEYORS OFFICE 2007
T 30 S R 5 W
S 31
CE 1/16

Markings on 1979 brass cap are ground off and blank brass cap now becomes an accessory for new position. 1979 BTs now become accessories for new position. W.Oak is rescribed/retagged, pistol butt D.fir is just retagged, as healed blazes generally point in correct direction

27" dia., W.Oak, double blazed & scribed "CE 1/16 S31 CS BT" bears S.83°W., 105.8 ft.

20" dia., pistol butt D.Fir (1979 BT) shows good healed blaze that points generally toward position, bears S.85°E., 61.4 ft.

2½" dia., blank brass cap, flush with ground, bears N.73°30'57"W., 149.22 ft.

Note - Lies approx. 40 ft. west of N-S fence on nearly level ground. Compass decl. 16¼°E.