

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200120

PRIMARY CORNER DESCRIPTION S. 1/16 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - Gary Langlitz; L.E. Monrean; Karen Reed; P. Earle; Vicki Woodral; F. Silagy - July 12, 1979 - C.S. File 61/3; RM 3-26

-----  
At position of S. 1/16 between Secs. 31 and 32 as determined by survey:

We Set a 1" x 36" I.P. with brass cap attached 30" in the ground mkd: Douglas County Surveyor T30S R5W S 1/16 S31 S32 1979.

New BT -7" Fir bears S.10°E., 35.0 ft. mkd. with double blaze "S 1/16 S32 CS" in upper blaze. "BT" in lower blaze.

No other trees suitable for scribing in area.

Corner is North approx. 70 ft. below old logging road going East and West on North slope.

-----  
Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 2/8/2007 - C.S. File 67/21-9 & M146-53

Found - 2½" dia., brass cap, properly marked on 1¼" O.D. iron pipe. Projects 7" above ground.  
7" now 20" dia., D.Fir fully healed blaze fd as per 1979 rec.

Set - 2½" dia., brass cap on 1¼" O.D. iron pipe 30" long BC projects 6" above ground.

**1979 brass cap is cut off & 1¼" O.D. iron pipe now becomes an accessory to the new position. BT tag is removed from 1979 BT.**

BC mkd: DOUGLAS CO SURVEYORS OFFICE  
T30S R5W  
S 1/16 S 31|S 32  
2007

9" dia., Pistol butt D.Fir double blazed & scribed "S 1/16 S31 CS BT" bears S.28½°W., 3.0 ft.

12" dia., D.Fir double blazed & scribed "S 1/16 S31 CS BT" bears N.50½°W., 43.1 ft.

9" dia., D.Fir double blazed & scribed "S 1/16 S32 CS BT" bears N.76½°E., 9.2 ft.

1¼" O.D. IP projects 5" above ground bears N.75°00'27"W., 293.5 ft.

Note - Corner lies 25 ft. easterly of overgrown logging rd. Compass decl. 16¼°E.