

Alias	Description

Doug. County Surveyors Office - Karen Reed; P. Earle; F. Silagy; Vicki Woodral - July 18, 1979 - C.S. File 61/3; RM 3-26

Found - 2" I.P., 1" above ground set by Wenderoth in 1946. Said pipe bears S.70°13'13"E., 99.54 ft. dist. from new position of N marked/16.
9" B.Oak bears N.40°W., 13.0 ft. (Rec. N.38°46'W., 12.7 ft.) with healed over blaze. (M 20-24)
10" B.Oak now 22" bears S.88°E., 46.5 ft. (Rec. S.83°36'E., 46.0 ft.) with healed over blaze. (M 20-24)

I.P. and trees left intact. This corner set in wrong position. Our survey of the area determined that surrounding corners are in wrong position, therefore, correction of these corners sets a new position for N. 1/16.

Set a 1" x 36" I.P. with brass cap mkd: "Douglas County Surveyor T30S R5W N 1/16 S31 S32 1979"

New BTs -22" B.Oak scribed "N 1/16 S31 CS BT" in a double blaze bears S.52°E., 17.6 ft.
10" Fir scribed "N 1/16 S32 CS BT" in a double blaze bears S.47°W., 15.2 ft.

Fd Brass Cap -James D. Artman, LS 2268 - For: David Ingwersen - March 1994 - M 118-51

Douglas Co. Surveyors Office - Stephen J. Flaue - John Pike - 1/3/2007 - C.S. File 67/21-2 & M146-53

Found - 1979 DCSO brass cap properly marked on 1¼" O.D. iron pipe projecting 6" above ground.
22" now 26" B.Oak, healed double blaze fd as per 1979 rec.
10" now 16" dia., x 2 ft. tall D.Fir stump, healed lower blaze, fd as per 1979 rec..

Set - 2½" dia., brass cap on 1¼" O.D.x30" iron pipe projects 7" above ground.

1979 brass cap was sawed off. Tags from BTs witnessing 1979 position were removed.

New brass cap mkd: DOUGLAS CO SURVEYORS OFFICE
T30S
R5W
S 31|S 32
N 1/16
2007

24" dia., B.Oak, double blazed & scribed "N1/16 S31 CS BT" bears N.87°W., 10.2 ft. (This tree also witnessed Wenderoth's position) cont next page

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200160

PRIMARY CORNER DESCRIPTION N 1/16 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

9" dia., D.Fir, double blazed & scribed, "N1/16 S32 CS BT" bears N.74°E., 5.4 ft.
2" I.D. iron pipe 1" above ground (Wenderoth, 1946) bears S.8°30'24"W., 9.11 ft.
1" I.D. iron pipe 4" above ground (Ingram, 1979) bears N.75°29'08"W., 98.17 ft.
Note - Corner bears approx. N.8°E., 9 ft. from fence corner. Fences extending East-West & North. Also lies near backyard of residence at 248 Evergreen Ridge Rd.
Compass decl. 16¼°E.