

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7153)

Set ¼ sec. post, from which
A B.Oak 30" dia., bears N.2½°W., 42 lks. dist.
A B.Oak 14" dia., bears N.75°E., 40 lks. dist.

John H. Markham, Jr. - For: Mr. Sharp - Wit: G and W. Vaughn
April 23, 1950 - C.S. File 40/250A-2

Determined from remains of O.B.T.
B.Oak 24" dia., bears N.75°E., 26.4 ft. This O.B.T., I
rescribe ¼S S29 BT.
A B.Oak stump bears N.2½°W., 26.0 ft.
At corner point, Set 2" x 2" Oak post, from which
A Laurel 8" dia., bears N.32°W., 7.0 ft. mkd. ¼S S30 2880
BT.
This is a fence running North, South and East from corner.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike
Darby; Jim Halterman - Oct./Nov. 1963 - C.S. File 53/26-28

Found - 3/8" Iron rod at corner.
Now 14" Laurel N.32°W., 7.0 ft. shows good bark
scribing.
Orig. NE BT, now snag.
Set Brass cap at cor. mkd: County Surveyor's Office, 1963
¼ S30 | S29 T30S R5W
New BT - 14" Fir bears N.71°E., 11.6 ft. scribed ¼ S29 CS BT.
Rescribe 14" Laurel, N.32°W., 7.0 ft. "¼ S30 CSBT."

Doug. County Surveyors Office - R. B. Kimberling; S.J. Flause
June 28, 1978 - C.S. File 60/11-23

Found - A 1" x 36" I.P. with brass cap set 12" above ground,
properly mkd. I reset from bearing and distance
to O.B.T.
A 14" now 22" 6 ft. high Oak snag bears N.75°E.,
26.4 ft. with scribing "BT" in new blaze. Orig.
blaze rotted away.
8" now 14" Madrone (Laurel) bears N.25°W., 10.2 ft.
(Rec. N.32°W., 7.0 ft.) with scribing "S3 -CS- T"
in a partly healed single blaze.
14" now 16" 4 ft. high Fir snag bears N.59°E., 12.1
ft. (Rec. N.71°E., 11.6 ft. with scribing "¼ S29
CS BT" in a single blaze. (Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Set - I reset brass cap at record bearing and distance to O.B.T., 6" above ground, stamped "Reset 1978".
I set a 5/8" x 30" I.R. at old brass cap location with Douglas Co. cap set at ground level and stamped "1978"
New BT -10" Madrone bears N.56½°E., 34.9 ft. I bark scribe "¼ S29 CS BT."
Corner is 9 ft. West of the intersection of a N-S barbed wire fence with a picket fence to the East.

Corner Fd. OK, by BLM resurvey, W. Rogers, under Group #1069 Surveyed Aug/Sept. 1981 (DCS0 records, Vol. 45 Page 17370)

DCS0-GIS Corner visitation - 1/12/2005 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 1.25" IP/BC
Comment - ok

Fd. BC per record by R. Brown, 10/2017 - M173-63