

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7153)

Set a post corner of secs. 19, 20, 29 and 30, from which
A B.Oak 4" dia., bears S.20°E., 30 lks.
A Laurel 18" dia., bears N.80°E., 60 lks.
A Laurel 15" dia., bears N.5°W., 42 lks.
A Maple 6" dia., bears S.70°W., 40 lks.

A.R. Evans - Wit: Kershner and Godfrey - For: E.E. Church - June 11, 1948 - C.S. File 39/181

One O.B.T. alive and standing, 30" Laurel N.5°W., 27.7 ft. Found stake set by State Hwy crew, checks for recorded bearing and distance. Use as temp. cor. Reset corner. Set 1" Galv. I.P. with brass cap mkd: County Surveyor's Office 19|20 T30S R5W
30|29

Scribed new BTs:

20" Fir N.19°E., 5.0 ft. mkd. S20 T30S R5W CS BT.
18" Fir S.52½°E., 10.4 ft. mkd. S29 T30S R5W CS BT.
20" Fir N.22°W., 22.2 ft. mkd. S19 T30S R5W CS BT.
18" Maple S.28 3/4°W., 70.1 ft. mkd. S30 T30S R5W CS BT.

(All marked also with R.E. 2741)

Doug. County Surveyors Office - James Byron, deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-20

Found - 18" now 20" Maple S.29°W., 70.1 ft. shows good scribing.
NE & SE BTs, now stumps. NW BT, now down.
Brass cap at corner Old logging road is South, 40 ft
New BTs -7" R.Fir bears N.2°W., 35.2 ft. scribed S19 T30S R5W CS BT.
10" B.Oak bears N.19°E., 58.5 ft. scribed S20 CS BT.
7" R.Fir bears S.54°E., 29.3 ft. scribed S29 T30S R5W CS BT.

Fd. OK, May 24, 1982, J.H. Markham, Jr., M 92-33
Fd. Brass cap as per record, R.Brown, May 1993, M 112-76 ABC

DCSO-GIS Corner visitation - 1/4/2005 - Typed: 2/8/2011 - C.S. File 67/33-1

Monument - 1.25" IP/BC Comment - ok

Fd. Brass cap as per record, R.Brown, May 2009, M157-13