

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7155)

Set ¼ sec. post, from which
A W.Oak 10" dia., bears S.25°E., 40 lks.
A B.Oak 12" dia., bears N.25°W., 15 lks.

Thiel - For: Thos. J. Hall and Ed Weaver - April 3, 1900 - Vol. 2 Page 88

Found old bearing trees standing. Set stone 12 x 8 x 6 for corner. Remarked SE tree.

G.G. Stewart, Deputy - Wit: J.M. Yocum; Ed Weaver; Vernon Weaver; Wm. Weaver - Dec. 16, 1921 - Vol. 3 Page 105; "old" Cor. Bk. Page 148

Found Mound of rocks. Reset from original BTs which were nearly destroyed by fire and rot. Set iron Pipe for corner, from which
36" B.Oak S.14½°E., 72.0 ft. (C.S. File 7/14 & Vol. 3 Pg. 105 says brg. is S.13°E.)
20" B.Oak N.69°E., 46.5 ft.

F.C. Frear; Jim Wolford; Gene Richardson - Sept. 17, 1942 (Could find no record source for this information)

Rifle barrel, from which
A B.Oak 24" bears N.69°E., 46.5 ft. (old BT)
A B.Oak 30" bears S.14½°W., 72.0 ft. (old BT)
A W.Oak 12" bears West, 11.3 ft. (new BT)
A Pine 12" bears N.33°E., 24.8 ft. (new BT)

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam - Feb. 2, 1960 - C.S. File 49/107-6

Found - 24" now 28" B.Oak N.69°E., 46.5 ft. previously opened, shows scribe mark.
Also fine base of rotted Pine, now 16" that checks bearing and distance for NE BT.
Now 14" Laurel bears N.62°E., 28.2 ft. shows good scribing "¼S". I add "20 CS BT".
Set brass cap at cor. mkd. County Surveyor's Office, 1960
¼ S19 | S20 T30S R5W
New BT - 12" B.Oak bears N.25½°W., 37.9 ft. scribed ¼ S19 CS BT.

