

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Pages 7156-57)

Set a post corner of secs. 7, 8, 17 and 18 from which
A W.Oak 24" dia., bears N.25°E., 31 lks.
A W.Oak 24" dia., bears N.55°W., 76 lks.
A W.Oak 8" dia., bears S.76°W., 67 lks.
A W.Oak 8" dia., bears S.5°E., 178 lks.

H.L. Eppstein - Wit: G.B. Nichols; J.W. and G.A. Fitzpatrick - Nov. 17, 1926 - Vol. 3 Pg. 277; C.S. File 6/48; and "old" Cor. Bk. Pg. 183

Renewed from two old BTs, NE., SE., and NW.
Set 1½" x 30" Iron pipe. Marked
A 14" W.Oak S.5°W., 163 lks. for tree gone in Section 18.

B.B. Irving, Co. Surveyor - For: J.E. and G.A. Firtzpatrick - April/May 1948 - M 20-23; C.S. File 39/171

Found - 1" I.P. in mound of rock.
36" W.Oak N.25°E., 20.5 ft. old BT.
15" W.Oak S.5°E., 117.5 ft. old BT.
18" W.Oak S.5°W., 107.6 ft. old BT.
Marked: 20" W.Oak N.70°W., 108.8 ft. scribed CS BT #2741.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby - Sept/Oct. 1963 - C.S. File 53/26-15

Found - 1" I.Pipe at corner.
20" W.Oak N.70°W., 108.8 ft. shows scribing.
Original SE and NE bearing trees.
New BTs -8" Laurel bears N.11°W., 11.4 ft. scribed T30S R5W S7 CS BT.
8" R.Fir bears S.19°E., 40.1 ft. scribed T30S R5W S17 CS BT.
Corner is in old N-S fence line 2" under surface and at North edge of old road.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15558-59)

The Sec. cor., perpetuated and recorded by Eppstein, 1926 and further perpetuated and recorded by Irving, 1948, and Byron, 1963, monumented with an iron pipe, 1½" dia., 30" long, firmly set, 2" below surface of ground, (Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7,8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remains of the original bearing trees:
A W.Oak 40" dia., bears N.27½°E., 34½ lks. dist., with
healed blaze. (Rec. N.25°E., 31 lks.)

A W.Oak 13" dia., bears S.1½°E., 178 lks. dist., with
fragmentary scribe marks visible on opened blaze. (Rec.
S.5°E.)

and a bearing tree by Eppstein:

A W.Oak 16" dia., bears S.9 3/4°W., 161½ lks. dist., with
healed blaze.

and a bearing tree mkd. by Irving:

A W.Oak 21" dia., bears N.70°W., 165½ lks. dist., with
scribe marks T30S R5W S7 CS 2741 BT visible on
partially healed blaze.

and bearing trees mkd. by Byron:

A Fir 10" dia., bears S.19 3/4°E., 61½ lks. dist., with
scribe marks T30S R5 visible on partially healed double
blaze.

A Madrone 9" dia., bears N.12½°W., 17½ lks. dist., with
scribe marks T30S R5W S7 CS BT visible on partially
healed double blaze.

At the Corner Point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, directly over iron pipe, with brass cap mkd:

T 30	S R 5 W
S 7	S 8
<hr/>	
S 18	S 17
1969	

Fd. Ok by D. Bentz, Oct. 1994 - 1994-107

Found OK By M.Farr, July 1997 - 1997-0095

Found OK by K. DeGroot, May 2003 - M142-21