

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7158)

Set a post corner of secs. 5, 6, 7 and 8.
Made a trench and drove a charred stake, 12" long at the center point as per instructions.

M. B. Germond - Wit: F.C. Frear; Hank Weaver - May 1917 - (Probably from survey recorded in Field Book 42 Pg. 27; Vol. 3 Pg. 42; C.S. File 7/9; M 1035, but, this wording only shown in "old" Cor. Bk. Pg. 145)

I set this corner in by proportional measurements. New corner is 1" x 48" buggy axle set 10" deep in the ground, from which a 3" Cedar stake bears N.45°E., 58 ft. Cedar stake is set in mound of stone.
A 3" Cedar stake bears S.45°E., 58 ft.

Doug. County Surveyors Office - James Byron, Deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-19

Found - 1¼" I.P., 3" under surface. Do not find axle set by Frear.
Note: See "Midway Tracts" Subdivision for location of this corner. (Plat, Vol. 10 Pg. 23)
No trees near.

Found OK by K. DeGroot, May 2003 - M142-21