

PRIMARY CORNER DESCRIPTION CW 1/16 Cor. Sec. 32

Alias	Description

Doug. County Surveyors Office - Gary Langlitz; Ed Monrean; Karen Reed; F. Silagy; P. Earle; Vicki Woodral - Aug. 8, 1979 - C.S. File 61/3; RM 3-26

-----  
At center of West 1/16 Cor. of Sec. 32, T30S R5W as determined by survey:

We Set a 5/8" x 30" Iron rod with alum. cap mkd: "C W 1/16 S32 C". Monument set 2" below surface.

New Accessories:

A bridge spike set in center line of paved road to county waste disposal site stamped "BO 1" bears S.5°16'02"W., 319.0 ft. Spike is set on line between CW 1/16 S32 and W 1/16 on South line of S.32.

A 5/8" I.R. with alum. cap stamped "BO 2" bears S.89°07'33"E., 135.0 ft. is on line between CW 1/16 S32. This monument is approx. 2 ft. West of a N-S fence line.

This corner is located in leveled graveled area as prepared for county stock pile.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 1/30/2007 - C.S. File 67/21-5 & M146-53

-----  
Found - 1979 monument not fd. (5/8" I.R. w/alum cap) Buried under gravel pile in county stockyard.

Bridge spike in center of Co. Rd. is fd. per rec. 5/8" I.R. w/alum cap stamped "BO 2" is fd. per rec.

Set - 2½" dia., brass cap on 1¼" O.D. iron pipe 30" long projects 6" above ground. BC MKD:

DOUGLAS CO SURVEYORS OFFICE

T30S

R5W

CW 1/16

S 32

2007

New - RM 3-26 calc point bears N.75°14'38"W., 145.70 ft 4" dia., Pine double blazed & scribed "X" bears North, 13.2 ft. ft.

10" dia., W.Oak double blazed & scribed "CW 1/16 S32 CS BT" bears S.36°E., 48.2 ft.

Note - Corner lies on nearly flat terrain, approx. N.35°E., 8 ft. from fence corner with fences extending North, South & East.

Compass decl. 16¼°E.