

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7152)

Set ¼ sec. post at average distance, from which
A Laurel 5" dia., bears S.5°E., 62 lks. dist.
A R.Fir 20" dia., bears N.60°W., 84 lks. dist.

John Markham, Jr. - For: Mr. Sharp - Wit: G. Vaughn & W. Vaughn - April 23, 1950 - C.S. File 40/250A-1

Determined from remains of original BT, a Fir 30" dia., bears S.60°W., 55.4 ft. scribe legible.
At corner point, Set a 1" x 30" I.Pipe, 24" in ground, from which:
A Laurel 8" dia., bears N.18°W., 18.5 ft. mkd. ¼S S29 2880 BT.

G. J. Wenderoth, Feb. 1953 - C.S. File 45/132; M 5-29

Set 1" Iron pipe.
30" Fir S.60°W., 55.4 ft.
10" Madrona N.12°16'W., 18.7 ft.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow - Dec. 5, 1957 - C.S. File 46/64

Found - 1" I.Pipe at corner.
The 30" Fir S.60°W., 55.4 ft. is low cut stump now, no scribing. Checks bearings and distances.
The 10" Madrona N.12°16'W., 18.7 ft. now dead, checks bearing and distances.
New BTs -18" R.Fir bears S.24°E., 10.2 ft. scribed ¼ S32 CSBT
13" R.Fir bears N.51°E., 8.2 ft. scribed ¼ S29 CSBT.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-29

Found - 1" I.Pipe at corner.
NE BT, OK. SE BT now dead.
New BT - 14" R.Fir bears S.5°W., 33.0 ft. ¼ S32 CS BT.

Doug. County Surveyors Office - Larry E. Monrean, Deputy - Karen Reed; Vicki Woodral - July 3, 1979 - C.S. File 61/3; RM 3-26

----- (Cont. Next Page)

