

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 240240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Wm. F. Briggs, April 1, 1892 - For: Dan Bollenbaugh - Vol. 1
Page 214; Field Book 4, Pg. 31-32

Set Post, marked C.S. BT., from which
A R.Fir 10" dia., bears S.56°W., 26 lks.
W.Oak 8" dia., bears S.10°W., 10 lks.

BLM survey, subd. of section by W. Rogers, under Group #1069
Surveyed, Aug./Sept. 1981 (DCSO records, Vol. 45 Pg. 17371)

Point for the center ¼ sec. cor. of sec. 29, at intersection
with the E. and W. center line.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd: T 30 S R 5 W
C 1/4
S 29
1981

from which
A twin Madrone 6" dia., bears S.8¼°E., 35½ lks. dist.,
mkd. C 1/4 S29 BT on bark.
A Maple 4" dia., bears S.69°W., 9 lks. dist., mkd. X BT.

DCSO-GIS Corner visitation - 1/13/2005 - Typed: 2/8/2011 -
C.S. File 67/33-1

Monument - 3" BC Comment - ok

Douglas Co. Surveyors Office - Stephen J. Flause - Mike
Koch - 10/8/2012 - C.S. File 67/36-41

CONDITION REPORT ONLY
BC monument in good cond.
BTs fd as described.
Renew BT tags and flagging as needed.