

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7154)

Set ¼ sec. post at average distance, from which
A B.Oak 10" dia., bears S.35°E., 10 lks. dist.
A B.Oak 10" dia., bears N.50°E., 18 lks. dist.

George C. Baker - L.S. #77 - C.S. File 40/6 (Who ?; Date ?)

I set a 4" squared Oak stake mkd. ¼, from the original trees as described. The tree in the NE is standing but dead, and the tree to the SW is down and rooten, scab shows scribing. I marked two new trees:
Fir 16" dia., bears S.58°20'E., 17.3 ft.
Fir 8" dia., bears S.22°30'W., 37.6 ft.

Doug. County Surveyors Office - James W. Byron, Deputy - Mike Darby; Jim Halterman - Oct. 1963 - C.S. File 53/26-22

Found - 4" x 4" scribed stake at corner and both BTs, all as described by Baker. BTs now dead, show scribing. Set Brass cap at cor. mkd: County Surveyor's ¼ S20 T30S R5W Office, 1963 S29
New BTs -22" Laurel, N.81°W., 22.8 ft. scribed ¼ S20 CS BT.
8" Laurel, S.23°E., 12.4 ft. scribed ¼ S29 CS BT.

Fd. brass cap as per record, R. Brown, May 1993, M 112-76 ABC

BLM resurvey by W. Rogers, under Group #1069 surveyed Aug/Sept. 1981. (DCSO records Vol. 45 Page(s) 17372)

The ¼ sec. cor. of secs. 20 and 29, perpetuated & recorded by Baker, in 1939, from original evidence no longer in existence, subsequently perpetuated and recorded by Byron, in 1969, monumented with an iron post, 1¼" diam., firmly set, projecting 16" above ground, with brass cap mkd,

COUNTY SURVEYORS OFFICE

T 30 S

¼ S 20

S 29

R 5 W

1963

from which the remains of a bearing tree mkd. by Baker
A burned fir snag, size indeterminate, bears S.22½°W., 57 lks., with illegible scribe marks visible on burned blaze.

and the remains of the bearing trees mkd. by Byron
continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

	<p>A root hole, bears S.23°E., 19 lks., with downed madrone alongside, 10" diam., with scribe marks ¼ S29 CS BT visible on open double blaze.</p> <p>A madrone snag, 22" diam., bears N.81°W., 30½ lks. with scribe marks ¼ S20 CS BT visible on open double blaze and new bearing trees</p> <p>A madrone, 8" diam., bears N.29°E., 25½ lks., mkd. ¼ S20 BT on bark.</p> <p>An oak, 5" diam., bears S.87°E., 31 lks., mkd. X BT. (Added to this renewal 2/28/2002)</p>
	<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/13/2002 - C.S. File 66/32-14 -----</p> <p>Found - 1963 DCSO brass cap iron pipe, protrudes 14" above ground. We set lower at plumb position, now protrudes 7" out of ground. No OBTs found. 8" now rotted to ground D.Fir scribing found "BT" bears S.22½°W., 37.6 ft. (CS 40/6) 16" now rotted to ground D.Fir no marks found bears S.58¼°E., 17.3 ft. (CS 40/6) 8" Madrone now clump of young Madrones, center of clump bears S.23°E., 12.4 ft. (1963) 22" now 22" dia., 12 ft. high Mad. snag with one live limb scribing visible "¼ S20 CS BT" bears N.81°W., 22.8 ft. (1963)</p> <p>New - 10" Madrone with BLM BT tag that reads S.29°W., 25½ lks., posted by WSR 8-81, faint visible bark scribing "¼ S20 BT" we double blaze & scribed "¼ S20 CS BT" bears N.27½°E., 16.8 ft. (1981 BLM) 6" dia., Madrone double blazed & scribed "¼ S29 CS BT" bears S.25½°W., 15.3 ft. Double trunked B.Oak double blazed & scribed "¼ S29 CS BT" on N'ly 9" trunk. Center of scribed trunk bears S.88½°E., 21.3 ft. (1981 rec. S.87°E., 20.5 ft. BLM) 11" dia., D.Fir double blazed & scribed "¼ S20 CS BT" bears N.74½°E., 55.0 ft. Compass decl. 17½°E</p>