

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7157)

-----  
Set ¼ sec. post at average distance, from which  
A Laurel 8" dia., bears S.75°E., 100 lks.  
A B.Oak 4" dia., bears N.35°W., 35 lks.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15560)

-----  
Point for the ¼ sec. cor. of secs.8 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: T 30 S R 5 W

¼     S 8  
       S 17

from which

An Oak 11", bears N.88°E., 61 lks. dist., mkd. ¼ S8 BT.  
An Oak 13", bears S.3¼°W., 50½ lks. dist., mkd. ¼ S17 BT.

Found OK by K. DeGroot, May 2003 - M142-21