

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7158)

Set ¼ sec. post at average distance, from which
A B.Oak 12" dia., bears S.20°W., 42 lks.
A W.Oak 10" dia., bears N.30°E., 41 lks.

M.B. Germond - Wit: F.C. Frear; Hank Weaver - May 1917 - (Probably from survey recorded in Field Book 42 pg. 27; Vol. 3 Pg. 42; C.S. File 7/9; M 1-35, but wording is from "old" Cor. Bk. Pg. 145

This corner is set on true line between section corners and at midway point. New corner is a 1" x 40" buggy axle, from which
A R.Fir 24" dia., bears S.48 ¾°E., 23.3 ft.
A R.Fir 24" dia., bears N.65¼°W., 43.0 ft.

Doug. County Surveyors Office - James Byron, Deputy - S.A. Bilow - April 24, 1959 - C.S. File 49/107-5

Found - Axle under E-W fence and both BTs, bark scribed, as recorded by Germond.
The NW BT, now stump. (Distances to BTs are on slope)
New BT - 10" W.Oak bears N.15½°W., 75.8 ft. scribed ¼ S5 CS BT.

Fd. OK, March 1987, R. Ware, C.S. File 58/272
Fd. OK, July 1994 by R. Brown, Partition Plat 1994-0060 A & B
Fd OK by K. DeGroot, May 2003 - M142-21