

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7149)

Set a post in the edge of the prairie corner of secs. 16, 17, 20 and 21, from which
A B.Oak 12" dia., bears S.47°E., 692 lks.
A B.Oak 12" dia., bears N.73°E., 756 lks.
A B.Oak 15" dia., bears N.8°W., 1050 lks.
Made a mound there being no tree convenient.

George J. Wenderoth - April 3, 1957 - C.S. file 47/170

Found - 30" B.Oak S.47°E., 456.7 ft., uprooted and rotten, scribe marks found.
Drive 1" Iron Pipe.
Scribe - 16" B.Oak S.83°12'E., 417.6 ft.
12" madrone N.56°35'E., 601.7 ft.

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 -Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Page 15547)

The Sec. Cor. perpetuated and recorded by Wenderoth in 1957, monumented with an iron pipe, 1" dia., 30" long, firmly set, projecting 4" above ground, from which BTs mkd. by Wenderoth:
A Madrone 18" dia., bears N.56½°E., 913½ lks. dist., with scribe marks S16 CS visible on partially healed double blaze.
A B.Oak 24" dia., bears S.83°E., 633 lks. dist., with healed double blaze.

At the Corner Point
Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:
T 30 S R 5 W
S 17 | S 16
S 20 | S 21
1969

from which
A Power pole 17" dia., bears S.29½°E., 78 lks., No. 6/29
A Power pole 14" dia., bears N.79½°W., 508 lks., No. 5/29.
No other suitable trees or objects available.
Reset iron pipe alongside iron post.

Fd. Brass cap as per record, R. Brown, May 1993, M 112-76 ABC
Fd. Ok by Kris DeGroot, 4/2006 - M 146-38 & M146-45
Fd. Ok by K DeGroot, 7/2006 - M146-42
Fd as per record - D Edwards - 9/2021 - 2021-0049C