

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7150)

-
- Set a post cor. of secs. 8, 9, 10 and 15, from which
- A B.Oak 8" dia., bears S.15°E., 116 lks.
 - A B.Oak 12" dia., bears N.35°E., 50 lks.
 - A B.Oak 20" dia., bears N.43°W., 46 lks.
 - A B.Oak 3" dia., bears s.65°W., 48 lks.

Fd. Oak post, 24" high, 4" sq. set evidently by the Co. Surveyor, mkd. and witnessed as described by the surveyor general. Fire has also been around here. By - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7186)

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15548-49)

Point for the cor. at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T	30	S	R	5	W	
		S	8		S	9
		S	17		S	16
						1969

from which

- A Pine 12" dia., N.57°E., 186 lks. mkd. T30S R5W S9 BT.
- A Madrone 13" dia., bears S.57½°E., 179 lks. mkd. T30S R5W S16 BT.
- A Pine 17" dia., bears S.43½°W., 244 lks. dist., mkd. T30S R5W S17 BT.
- A Fir 13" dia., bears N.26°W., 148 lks. dist. mkd. T30S R5W S8 BT.

BLM resurvey by Wayne L. Rogers, under Contract #s 1000 and 1342 - Surveyed Aug. 1986 (DCSO records, Vol. 48 Pages 18350-51)

The Sec. cor. determined at record bearing and distance from bearing trees mkd. by Roseberry and Jelley:

- A Pine 18", bears N.57°E., 186 lks. with healed blaze.
- A Madrone 16", bears S.57½°E., 179 lks. with healed blaze.
- A Pine 22", bears S.43½°W., 244 lks. with healed blaze.
- A Fir 20", bears N.26°W., 148 lks. with healed blaze.

At the Corner Point

Set a stainless post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T 30 S R 5 W <u>S 8 S 9</u> S 17 S 16 1986</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. The corner is located North, 0.05 chs. dist. from a woven wire fence, extending E. and W.; West, 0.85 chs. to corner of fences extending S. and E.</p>
<p>Fd. Ok by K DeGroot, 7/2006 - M146-42 Fd. Ok by D. Edwards 1/2008 - M154-73</p>