

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7151)

Set ¼ sec. post, from which
A W.Oak 30" dia., bears s.75°E., 41 lks.
A W.Oak 7" dia., bears N.47°W., 48 lks.

Corner post found badly decayed on the outside; marked and witnessed as described by the surveyor general - by Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7186)

BLM resurvey by Lynn Roseberry & James Jelley, under Group #662 - Surveyed Oct. 1967/June 1969 (DCSO records, Vol. 38 Pages 15550-51)

Point for the ¼ sec. cor., re-established by the irregular boundary method, based on the 1896 Thiel survey.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 30 S R 5 W
¼
S 8 | S9
1969

from which
A Fir 13" dia., bears N.62½°E., 213 lks. mkd. ¼ S BT
A Madrone 4" dia., bears S.72¾°W., 67 lks. mkd. ¼ S8 BT.

BLM resurvey by Wayne L. Rogers, under Group #'s 1000 and 1342 - Surveyed Aug. 1896 (DCSO records, Vol. 48 Page 18351)

The ¼ sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with properly mkd. 1969 brass cap.

from which the remains of bearing trees mkd. by Roseberry and Jelley:

A Fir snag 14" dia., bears N.62½°E., 213 lks. with scribe marks ¼ S9 BT.
A Madrone 12" dia., bears S.72 3/4°W., 51 lks. dist., with healed blaze. (Rec. 67 lks.)

and a new bearing tree:

A Pine 7" dia., bears S.76°E., 17 lks. dist., mkd. ¼ S9 BT

Found OK by K. DeGroot, May 2003 - M142-21
Fd. Ok by D. Edwards 1/2008 - M154-73