

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Page 7151)

-----  
Set a post corner of secs. 4, 5, 8 and 9, from which  
An Alder 15" dia., bears N.20°E., 150 lks.  
A B.Oak 8" dia., bears N.35°W., 233 lks.  
Impracticable to make mound.

Original - Oscar F. Thiel, under Contract #658 dated May 21, 1896 (DCSO records, Vol. 17 Page 7186 and 7187)

-----  
The post for cor. of secs. 4, 5, 8 and 9, being gone, but the old bearing trees remaining, I re-establish the cor. by setting a Maple post, 3 ft. long, 5" sq., 24" in the ground, mkd. T30S S4 on NE., R5W S9 on SE., S8 on SW., and S5 on NW. faces with 5 notches on E. edges; from which  
An Alder 15" dia., bears N.20°E., 150 lks. mkd. T30S R5W S4 BT. (OBT)  
A B.Oak 8" dia., bears N.35°W., 233 lks. dist., mkd. T30S R5W S5 BT. (OBT)  
A W.Oak 6" dia., bears S.41½°W., 55 lks. dist., mkd. T30S R5W S8 BT. (New BT)  
A W.Oak 6" dia., bears S.22 3/4°E., 93 lks. dist., mkd. T30S R5W S9 BT. (New BT)

M. B. Germond - Wit: F.C. Frear and Hank Weaver - May 1917 - (Probably from survey recorded in F.B. 42 Pg. 27+; Vol. 3 Pg. 42; C.S. File 7/9 and M 1-35, but this wording for corner only found in "old" Cor. Bk. Page 145)

-----  
I reset this corner from testimony of Cleal Weaver and John Dicks as well as from BTs set in by Oscar Thiel  
I renew corner with a 3/4" x 30" galv. I.P., from which  
A W.Oak 6" dia., bears N.42°10'E., .065 chs.  
A W.Oak 12" dia., bears N.26°50'W., .105 chs.  
A W.Oak 7" dia., bears S.9°25'E., .035 chs.  
I also note that the stump of the trees marked by O. Thiel bears as follows:  
A W.Oak stump bears S.16°30'E., 91½ lks.  
A W.Oak stump bears S.40°20'W., 50 lks.

Doug. County Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow - March 13, 1959 - C.S. File 49/107-2

-----  
Found - 3/4" I.P. at corner.  
(Cont. Next Page)

